

# County Surveyor's Record, Douglas County, Oregon

18262

Subdivision of Section 22,  
T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir, 4 ins. diam., bears N.  $10\frac{1}{2}^\circ$  E.,  $22\frac{1}{2}$  lks. dist., mkd. X at breast height and BT at base.

A fir, 8 ins. diam., bears S.  $39\frac{1}{2}^\circ$  W., 37 lks. dist., mkd.  $\frac{1}{4}$  S22 BT.

From the  $\frac{1}{4}$  sec. cor. of secs. 22 and 23, monumented with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set, protruding 4 ins. above ground with brass cap mkd.

T 28 S R 8 W  
S 22 | S 23  
1975

from which the bearing trees mkd. by Jelley

A fir, 10 ins. diam., bears N.  $50\frac{1}{2}^\circ$  E., 12 lks. dist., with healed blaze.

A fir, 9 ins. diam., bears N.  $79^\circ$  W., 20 lks. dist., with healed blaze.

S.  $89^\circ 06'$  W., on the E. and W. center line of sec. 22.

Ascend over steep broken NE. slope.

20.09 Point for the center E  $\frac{1}{16}$  sec. cor. of sec. 22.

Set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

C  $\frac{E \frac{1}{16}}{S 22}$  C  
1985

from which

A grand fir, 26 ins. diam., bears S.  $46^\circ$  W., 31 lks. dist., mkd. CE  $\frac{1}{16}$  S22 BT.

A fir, 4 ins. diam., bears N.  $62\frac{1}{2}^\circ$  W., 28 lks. dist., mkd. X BT.

Ascend over broken E. slope.

28.10 Top of ascent, slopes N.; desc. over broken NW. slope.

39.90 Bottom of descent, bears NE. and SW.; enter nearly level swampy area.

40.18 The center  $\frac{1}{4}$  sec. cor. of sec. 22.

S.  $89^\circ 49'$  W., beginning new measurement.

Descend over nearly level swampy area.

2.00 Begin descent over W. slope.

6.30 Creek, 10 lks. wide, course N.  $50^\circ$  W.; asc. over steep E. slope.

8.10 Spur, slopes NW.; desc. over broken NW. slope.

38.65 Trail, 15 lks. wide, bears NE. and SW.