

County Surveyor's Record, Douglas County, Oregon

18271

Subdivision of Section 35,
T. 24 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
20.175	<p>Point for the center S 1/16 sec. cor. of sec. 35.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>C S 1/16 S 35 C 1986</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 66° E., 49 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 43 3/4° W., 9½ lks. dist., mkd. CS 1/16 S35 BT.</p> <p style="padding-left: 40px;">Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a point unofficially established by L. W. Barber, Federal Highway Administration, in 1974, bears S. 1° 45' W., 0.14 chs. dist., monumented with an iron rod, ½ in. diam., firmly set, projecting 4 ins. above ground.</p> <p>Ascend over broken SE. slope.</p>
22.90	Spur, slopes N. 75° E.; continue to asc. over broken SE. slope.
39.85	Spur, slopes SE.; desc. over NE. slope.
40.35	<p>Point for the center 1/4 sec. cor. of sec. 35, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 S R 4 W C¼ S 35 1986</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 62° E., 21 lks. dist., mkd. C¼ S35 BT.</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears S. 9¼° E., 31 lks. dist., mkd. C¼ S35 BT.</p> <p style="padding-left: 40px;">Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a point unofficially established by L. W. Barber, Federal Highway Administration, in 1974, filed in the County Surveyor's Records, in 1984, bears S. 13° 11' E., 0.26 chs. dist., monumented with an iron rod, ½ in. diam., firmly set, projecting 2 ins. above ground.</p> <p>Descend over NE. slope.</p>
47.00	Ravine, drains S. 50° E.; asc. over broken SE. slope.
55.60	Gravelled road, 20 lks. wide, bears N. 75° E. and S. 75° W.
55.90	Ridge, bears N. 35° E. and S. 35° W.; desc. over NW. slope.