

# County Surveyor's Record, Douglas County, Oregon

18274

Subdivision of Section 35,  
T 24 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 32 ins. diam., bears N. 76° W., 51 lks. dist., with fragmentary scribe marks visible on a partially healed blaze.</p>
	<p>From the center E 1/16 sec. cor. of sec. 35.</p> <p>N. 0° 09' E., on the N. and S. center line of the NE<math>\frac{1}{4}</math> of sec. 35.</p> <p>Ascend over broken SE. slope.</p>
1.90	Top of ascent; desc. over broken E. slope.
11.50	Creek, 1 lk. wide, course SE.; asc. over SW. slope.
25.20	Spur, slopes N. 60° E.; desc. over NE. slope.
32.05	Ravine, drains E.; asc. over SE. slope.
39.45	Spur, slopes N. 60° E.; desc. over NW. slope.
40.10	The E 1/16 sec. cor. of secs. 26 and 35.
	<p>From the center S 1/16 cor. of sec. 35.</p> <p>N. 89° 59' W., on the E. and W. center line of the SW<math>\frac{1}{4}</math> of sec. 35.</p> <p>Ascend over broken SE. slope.</p>
22.65	Ridge, bears N. 50° E. and S. 50° W.; desc. over SW. slope. changing to a broken NW. slope.
39.30	Woven wire fence, bears N. and S.
39.62	The S 1/16 sec. cor. of secs. 34 and 35, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.
	<p>S 1/16 S 34   S 35 1985 1972</p>
	<p>from which bearing trees mkd. by Bishop and White</p> <p>A fir, 8 ins. diam., bears N. 40° E., 37 lks. dist., with scribe marks S 1/16 S35 BT visible on partially healed blaze.</p> <p>A fir, 10 ins. diam., bears N. 85 3/4° W., 42 lks. dist., with scribe marks S 1/16 S34 BT visible on partially healed blaze.</p>
	<p>From the center W 1/16 sec. cor. of sec. 35.</p> <p>N. 0° 04' E., on the N. and S. center line of the NW<math>\frac{1}{4}</math> of Sec. 35.</p> <p>Descend over broken NW. slope, through heavy timber and dense undergrowth.</p>
1.25	Gravelled road, 20 lks. wide, bears N. 70° E., and S. 30° W., in curve.