

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 35,
T. 24 S., R. 4 W., Willamette Meridian, Oregon

18275

CHAINS	
4.30	Creek, 1 lk. wide, course S. 70° W.; asc. over SE. slope
12.80	Spur, slopes S. 80° E., to saddle; desc. over broken NE. slope.
13.40	Dirt road, 15 lks. wide, bears N. 50° W. and S. 50° E.
19.855	Point for the NW 1/16 sec. cor. of sec. 35, at intersection with the E. and W. center line of the NW¼. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. NW 1/16 S 35 1986 from which A maple, 24 ins. diam., bears N. 80½° E., 48 lks. dist., mkd. NW 1/16 S35 BT. A fir, 32 ins. diam., bears S. 28 3/4° E., 55 lks. dist., mkd. NW 1/16 S35 BT. Deposit white "DEEP-1" magnetic marker at base of stainless steel post. Descend over NE. slope.
20.20	Creek, 2 lks. wide, course N. 70° W.; asc. over SW. slope.
29.00	Spur, slopes S. 50° W.; desc. over NW. slope.
39.60	Creek, 1 lk. wide, course W.; asc. over SE. slope.
39.71	The W 1/16 sec. cor. of secs. 26 and 35, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground with brass cap mkd. W 1/16 $\frac{S\ 26}{S\ 35}$ 1985 1972 from which the bearing trees mkd. by Bishop and White A fir, 10 ins. diam., bears N. 3° E., 96 lks. dist., with scribe marks W 1/16 S26 BT visible on open blaze. A fir, 7 ins. diam., bears S. 40½° E., 82 lks. dist., with scribe marks W 1/16 S35 BT visible on open blaze.
	From the center N 1/16 cor. of sec. 35. S. 89° 41' W., on the E. and W. center line of the NW¼ of sec. 35. Descend over broken NW. slope.
10.25	Ravine, drains S. 64° W.; continue descent along broken S. slope.
19.60	Creek, 3 lks. wide, course N. 50° W.; asc. over broken N. slope.
19.85	The NW 1/16 sec. cor. of sec. 35. Ascend along broken N. slope.
39.53	Woven wire fence, bears N. 25° E. and S. 25° W.