

# County Surveyor's Record, Douglas County, Oregon

Corrective Dependent Resurvey of  
A Portion of the East Boundary,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon

18279

**CHAINS**

(Restoring the survey by Thomas H. Hutchinson,  
in 1857, and correcting the resurvey by  
Floyd A. Brooks and Peter A. Peterson, in 1964)

Beginning at the cor. of secs. 13, 18, 19, and 24, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 23 S	
R 8 W	R 7 W
S 13	S 18
S 24	S 19
1964	

from which the remains of an original bearing tree.

A rotted fir snag, size indeterminate, bears  
N. 45° E., 17 lks. dist., no marks visible.

and the remains of bearing trees mkd. by Brooks and Peterson

A fir, 17 ins. diam., bears N. 34½° E., 27  
lks. dist., with healed blaze.

A fir, 18 ins. diam., bears S. 69½° E., 71  
lks. dist., with healed blaze.

A fir stump, size indeterminate, bears  
S. 71½° W., 98 lks. dist., no marks visible.

A fir, 33 ins. diam., bears N. 70° W., 96  
lks. dist., with healed blaze.

and a new bearing tree

An alder, 11 ins. diam., bears S. 23 3/4° W., 77  
lks. dist., mkd. T23S R8W S24 BT.

N. 0° 05' 30" W., bet. secs. 13 and 18, marking and blazing the true line.

Descend over N. slope, through scattering timber and moderate undergrowth.

2.20 Mehl Creek, 25 lks. wide, course E.; asc. over SE. slope.

22.60 Spur, slopes E.; desc. over NE. slope.

39.210 Point for the ¼ sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.

From this point, the ¼ sec. cor. of secs. 13 and 18, erroneously positioned by Brooks and Peterson, bears N. 78° 33' E., 0.632 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set projecting 4 ins. above ground, with brass cap mkd. and witnessed as described in the official record.

I remove the iron post, destroy the marks on the bearing trees, and at the true corner point

Reset the iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

¼	
S 13	S 18
T 23 S	
R 8 W	R 7 W
1986	