

# County Surveyor's Record, Douglas County, Oregon

18280

Corrective Dependent Resurvey of  
A Portion of the East Boundary,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which</p> <p style="margin-left: 40px;">A hemlock, 24 ins. diam., bears N. 87½° E., 96 lks. dist., mkd. ¼ S18 BT.</p> <p style="margin-left: 40px;">A fir, 30 ins. diam., bears N. 60° W., 82 lks. dist., mkd. ¼ S13 BT.</p> <p>Descend over NE. slope.</p>
46.05	Mehl Creek, 30 lks. wide, course NW.; asc. over SW. slope.
52.00	Creek, 1 lk. wide, course W.; asc. over SW. slope.
58.815	<p>Point for the N 1/16 sec. cor. of secs. 13 and 18.</p> <p>From this point, the N 1/16 sec. cor. of secs. 13 and 18, erroneously positioned by Brooks and Peterson, bears N. 81° 27' E., 0.941 chs. dist., monumented with a steel bridge spike, ¼ in. diam., firmly set, buried 4 ins. below surface of Mehl Creek Road.</p> <p>I remove the steel spike, destroy the marks on the NE. bearing tree, remove the referencemonument, and at the true corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam. 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>N 1/16 S 13   S18 1986</p> </div> <p>from which a bearing tree mkd. by Brooks and Peterson</p> <p style="margin-left: 40px;">A white fir, 28 ins. diam., bears S. 13½° E., 147 lks. dist., with scribe marks N 1/16 S18 BT visible on open blaze.</p> <p>and a new bearing tree</p> <p style="margin-left: 40px;">A white fir, 13 ins. diam., bears S. 28½° W., 126 lks. dist., mkd. N 1/16 S13 BT.</p> <p>Ascend over SW. slope.</p>
59.75	Mehl Creek Road, 35 lks. wide, bears N. 50° W. and S. 50° E.
78.420	<p>The cor. of secs. 7, 12, 13, and 18, determined at record bearing and distance from the remains of an original bearing tree:</p> <p style="margin-left: 40px;">A rotted fir stump, size indeterminate, bears S. 60° E., 30 lks. dist., with axe marks and chaining notch visible on open blaze.</p> <p>From this point, the cor. of secs. 7, 12, 13, and 18, erroneously accepted as original by Brooks and Peterson, bears N. 80° 37' E., 1.161 chs. dist., monumented with an iron post, 3½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. and witnessed as described in the official record.</p> <p>I remove the iron post, destroy the marks on the bearing trees, and at the true corner point</p> <p>Reset the iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 23 S R 8 W      R 7 W S 12   S 7 S 13   S18 1986</p> </div>