

# County Surveyor's Record, Douglas County, Oregon

Corrective dependent Resurvey of  
A Portion of the East Boundary  
T. 23 S., R. 8 W., Willamette Meridian, Oregon

18281

CHAINS																
	<p>from which new bearing trees</p> <p>A fir, 10 ins. diam., bears N. 19 3/4° E., 33 lks. dist., mkd. T23S R7W S7 BT.</p> <p>A fir, 15 ins. diam., bears S. 80 1/2° E., 34 lks. dist., mkd. T23S R7W S18 BT.</p> <p>A fir, 14 ins. diam., bears S. 51 3/4° W., 56 lks. dist., mkd. T23S R8W S13 BT.</p> <p>A fir, 13 ins. diam., bears N. 72 1/4° W., 55 lks. dist., mkd. T23S R8W S12 BT.</p> <p>Land, mountainous. soil, sandy clay loam. Timber, fir, cedar, hemlock, oak, maple and alder; undergrowth vine maple, poison oak, Oregon grape, salal, and ferns.</p>															
	<p>Corrective Dependent Resurvey of A Portion of the Subdivisional Lines, T. 23 S., R. 8 W., Willamette Meridian, Oregon</p>															
	<p>(Restoring the survey by Dennis Hathorn, in 1857, and correcting the resurvey by James E. Jelley, in 1970)</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp.</p> <p>N. 89° 23' 00" W., bet. /secs. 12 and 13, marking and blazing the true line.</p> <p>Descend over SW. slope, through scattering timber and dense undergrowth.</p>															
31.20	Mehl Creek Road, 30 lks. wide, bears N. 50° W. and S. 50° E.															
33.25	Mehl Creek, 10 lks. wide, course N. 40° W.; asc. over broken E. slope.															
40.375	<p>Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>From this point, the 1/4 sec. cor. of secs. 12 and 13, erroneously positioned by Jelley, bears S. 65° 40' E., 0.660 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, pro- jecting 4 ins. above ground, with brass cap mkd. and witnessed as described in the official record.</p> <p>I remove the iron post, and at the true corner point</p> <p>Reset the iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>															
	<table style="margin: auto;"> <tr> <td style="text-align: center;">1/4</td> <td style="text-align: center;">S 12</td> <td style="text-align: center;">ENO. 10/91</td> </tr> <tr> <td></td> <td style="text-align: center;">S 13</td> <td style="text-align: center;">BY</td> </tr> <tr> <td></td> <td></td> <td style="text-align: center;">R [UNLAW]</td> </tr> <tr> <td></td> <td style="text-align: center;">T 23 S R 8 W</td> <td style="text-align: center;">MLP # 1991-0067</td> </tr> <tr> <td></td> <td style="text-align: center;">1986</td> <td></td> </tr> </table>	1/4	S 12	ENO. 10/91		S 13	BY			R [UNLAW]		T 23 S R 8 W	MLP # 1991-0067		1986	
1/4	S 12	ENO. 10/91														
	S 13	BY														
		R [UNLAW]														
	T 23 S R 8 W	MLP # 1991-0067														
	1986															
	from which bearing trees mkd. by Jelley															