

# County Surveyor's Record, Douglas County, Oregon

Corrective Survey of the Subdivision of  
Section lines of Section 13,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon

18285

CHAINS	
	<p>from which the original bearing trees</p> <p style="margin-left: 40px;">A madrone, 26 ins. diam., bears S. 65° E., 9 lks. dist., with open blaze, no marks visible.</p> <p style="margin-left: 40px;">A fir, 45 ins. diam., bears S. 79° W., 65 lks. dist., with opened and rotted blaze. no marks visible.</p> <p>and bearing trees mkd. by Vernon Tracy, Deputy County Surveyor, in 1967</p> <p style="margin-left: 40px;">A madrone, 11 ins. diam., bears S. 59° E., 56 lks. dist., with scribe marks <math>\frac{1}{4}</math> S13 CS BT visible on partially healed blaze.</p> <p style="margin-left: 40px;">A fir, 10 ins. diam., bears S. 23<math>\frac{1}{2}</math>° W., 49 lks. dist., with illegible scribe marks on partially healed blaze. (Record S. 25° W.)</p> <p style="margin-left: 40px;">A fir, 12 ins. diam., bears N. 83° W., 16 lks. dist., with partially healed blaze, no marks visible.</p> <p>and a bearing tree of no record</p> <p style="margin-left: 40px;">A fir, 31 ins. diam., bears N. 63° W., 48 lks. dist., with healed blaze.</p>
<p>6.65</p> <p>25.60</p> <p>40.510</p>	<p>From the N 1/16 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp.</p> <p>S. 89° 36' 30" W., on the E. and W. center line of the NE<math>\frac{1}{4}</math> of Sec. 13.</p> <p>Descend over W. slope, through heavy timber and dense undergrowth.</p> <p>Mehl Creek, 15 lks. wide, course N.; asc. over broken E. slope.</p> <p>Ravine, drains N. 30° E.; asc. over NE. slope.</p> <p>The center N 1/16 sec. cor. of sec. 13.</p>
	<p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 23 S., R. 8 W., Willamette Meridian, Oregon</p>
	<p style="text-align: center;">(Restoring the survey by Williams. R. Whipple, in 1894)</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the <math>\frac{1}{4}</math> sec. cor. of Secs. 27 and 28, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1966, monumented with an iron post, 1<math>\frac{1}{2}</math> ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">DOUGLAS COUNTY SURVEYORS OFFICE T 23 S R <math>\frac{1}{4}</math> S 28   S 27 8 W 1966</p> <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A fir stump, 40 ins. diam., bears S. 66° E., 18 lks. dist., no marks visible.</p> <p style="margin-left: 40px;">A fir stump, 54 ins. diam., bears West, 4 lks. dist., no marks visible.</p>