

County Surveyor's Record, Douglas County, Oregon

18287

Dependent Resurvey, Portion of Subdivisional Lines,
T. 23 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

No other suitable trees available.

Land, mountainous.

Soil, clay loam and rocky.

Timber, fir, cedar, hemlock, alder, maple, and myrtle;
undergrowth, huckleberry, Oregon grape, salal, rhododendron,
salmonberry, ocean spray, hazel, and ferns.

From the $\frac{1}{4}$ sec. cor. of secs. 28 and 29, mkd. with the
original cross (X) and $\frac{1}{4}$ on near vertical face of exposed
bedrock, approximately 10 ft. high, 40 ft. long, bears
N. 20° W., and S. 20° E.

At the corner point

Set an iron post, 24 ins. long, 1 in. diam., 6 ins. in
drill hole in solid rock, with brass cap mkd.

T 23 S R 8 W
 $\frac{1}{4}$
S 29 | S 28
1986

from which

A fir, 31 ins. diam., bears S. 69 $\frac{1}{4}$ ° E., 28
lks. dist., mkd. $\frac{1}{4}$ S28 BT.

A fir, 25 ins. diam., bears S. 16° W., 29
lks. dist., mkd. $\frac{1}{4}$ S29 BT.

From this point, a witness cor. to the $\frac{1}{4}$ sec. cor. of
secs. 28 and 29, established and recorded by Vernon R.
Tracy, Deputy County Surveyor, in 1967, bears North,
0.150 chs. dist., monumented with an iron post, 1 $\frac{1}{2}$ ins.
diam., firmly set, projecting 8 ins. above ground, with
brass cap mkd.

DOUGLAS COUNTY SURVEYORS OFFICE
T 23 S
 $\frac{1}{4}$
WC 10 FT
S 29 | S 28
R 8 W
S TO COR
1967

from which bearing trees mkd. by Tracy

A fir, 15 ins. diam., bears S. 62 $\frac{1}{2}$ ° E., 33
lks. dist., with healed blaze.

A fir, 16 ins. diam., bears N. 71° W., 13
lks. dist., with healed blaze.

N. 0° 14' 30" E., bet. secs. 28 and 29.

Ascend over broken SW. slope, through moderate timber and
dense undergrowth.

20.120

Point for the N 1/16 sec. cor. of secs. 28 and 29.