

County Surveyor's Record, Douglas County, Oregon

18288

Dependent Resurvey, Portion of Subdivisional Lines,
T. 23 S., R.8 W., Willamette Meridian, Oregon

CHAINS

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ons diam, 22 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

N 1/16
S 29 | S 28
1986

from which

A fir, 6 ins. diam., bears S. $59\frac{1}{4}^{\circ}$ E., 34 lks. dist., mkd. X BT.

A fir, 8 ins. diam., bears S. $15\frac{3}{4}^{\circ}$ W., 13 lks. dist., mkd. N 1/16 S29 BT.

Ascend over SW. slope.

40.240

The cor. of secs. 20, 21, 28, and 29, perpetuated and recorded by Vernon R Tracy, Deputy County Surveyor, in 1966, monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

DOUGLAS COUNTY SURVEYORS OFFICE

T 23 S
S 20 | S 21
S 29 | S 28
R 8 W
1966

from which an original bearing tree

A fir, 78 ins. diam., bears N. 76° W., 65 lks. dist., with open blaze, no marks visible.
(Record, 69 lks.)

and bearing trees mkd. by Tracy

A hemlock, 21 ins. diam., bears N. $44\frac{1}{2}^{\circ}$ E., 41 lks. dist., with healed blaze.

A hemlock, 10 ins. diam., bears S. $27\frac{1}{2}^{\circ}$ E., 29 lks. dist., with healed blaze.

A hemlock, 10 ins. diam., bears S. 31° W., 37 lks. dist., with scribe marks T23S R8W S29 CS BT visible on open blaze.

A hemlock, 22 ins. diam., bears N. 79° W., 21 lks. dist., with healed blaze.

and a bearing tree of no record

A hemlock, 22 ins. diam., bears S. $15\frac{3}{4}^{\circ}$ E., 12 lks. dist., with healed blaze.

Land, mountainous.

Soil, clay loam and rocky.

Timber, fir, hemlock, cedar, alder, tanoak, maple, and myrtle; undergrowth, huckleberry, salal, Oregon grape, rhododendron, ferns, and grasses.

From the cor. of secs. 21, 22, 27, and 28.

S. $89^{\circ} 36' 30''$ W., bet. secs. 21 and 28.

Ascend over SE. slope, through heavy timber and moderate undergrowth.