

# County Surveyor's Record, Douglas County, Oregon

18289

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon

CHAINS										
8.70	Spur, slopes N. 40° E.; desc. over NW. slope.									
20.005	Point for the E 1/16 sec. cor. of secs. 21 and 28.  Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td style="padding-right: 10px;">E 1/16</td> <td style="border-left: 1px solid black; padding-left: 5px;">S 21</td> <td></td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 5px;">S 28</td> <td></td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 5px;"></td> <td style="text-align: center;">1986</td> </tr> </table> </div> from which  A fir, 19 ins. diam., bears N. 39½° E., 31 lks. dist., mkd. E 1/16 S21 BT.  A fir, 14 ins. diam., bears S. 65° W., 15 lks. dist., mkd. E 1/16 S28 BT.  Ascend over NE. slope.	E 1/16	S 21			S 28				1986
E 1/16	S 21									
	S 28									
		1986								
20.50	Spur, slopes N.; desc. over NW. slope.									
24.00	Creek, 1 lk. wide, course N.; asc. over NE. slope.									
28.30	Top of ascent, slopes N.; desc. over NW. slope.									
31.90	Ravine, drains N.; asc. over SE. slope.									
40.010	The ¼ sec. cor. of secs. 21 and 28, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1966, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.  <div style="text-align: center;"> <p>DOUGLAS COUNTY SURVEYORS OFFICE</p> <p>T 23 S</p> <table style="margin: auto;"> <tr> <td style="padding-right: 10px;">¼</td> <td style="border-left: 1px solid black; padding-left: 5px;">S 21</td> <td style="padding-left: 10px;">R</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 5px;">S 28</td> <td style="padding-left: 10px;">8</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 5px;"></td> <td style="padding-left: 10px;">W</td> </tr> </table> <p>1966</p> </div> from which the remains of the original bearing trees  A fir snag, 45 ins. diam., bears N. 79° E., 27 lks. dist., with scribe marks ¼ S visible on open blaze.  A burned cedar stump, indeterminate diam., bears S. 55° W., 9 lks. dist., no marks visible. (Record, S. 55° E.)  and bearing trees mkd. by Tracy  A hemlock, 27 ins diam., bears S. 70° E., 58 lks. dist., with healed blaze.  A hemlock, 13 ins. diam., bears N. 42° W., 31 lks. dist., with scribe marks ¼ S21 CS visible on partially healed blaze.  <hr style="width: 20%; margin: 10px auto;"/> N. 89° 42' 00" W., beginning new measurement.  Ascend over E. slope, through heavy timber and light undergrowth.	¼	S 21	R		S 28	8			W
¼	S 21	R								
	S 28	8								
		W								
11.15	Top of ascent, slopes N.; desc. over NW. slope.									
18.75	Waggoner Creek Road, 30 lks. wide, bears N. 70° W. and S. 70° E. asc. over E. slope.									