

County Surveyor's Record, Douglas County, Oregon

18290

Dependent Resurvey, Portion of Subdivisional Lines,
T. 23 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
19.925	<p>Point for the W 1/16 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $\begin{array}{r} \text{W } 1/16 \quad \frac{\text{S } 21}{\text{S } 28} \\ 1986 \end{array}$ </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 13 ins. diam., bears S. 6° W., 34½ lks. dist., mkd. W 1/16 S28 BT</p> <p style="margin-left: 40px;">A fir, 12 ins. diam., bears N. 54½° W., 39 lks. dist., mkd. W 1/16 S21 BT.</p> <p>Ascend over E. slope.</p>
34.50	<p>Dirt road, 15 lks. wide, bears S. 10° E. and N. 10° W.; desc. over W. slope.</p>
37.10	<p>Head of ravine, drains N. 65° W.; asc. over NE. slope.</p>
39.850	<p>The cor. of secs. 20, 21, 28, and 29.</p> <p>Land, mountainous. Soil, clay loam and rocky. Timber, fir, cedar, alder, maple, madrone, hemlock, and myrtle; undergrowth, huckleberry, vine maple, Oregon grape, salal, ferns, and grasses.</p>
<p>Subdivision of Section 28, T. 23 S., R. 8 W., Willamette Meridian, Oregon</p>	
<p>From the ¼ sec. cor. of secs. 28 and 33, monumented with the original sandstone, 16 x 13 x 7 ins. (Record, 14 x 10 x 5 ins.) firmly set 4 ins. in the ground, mkd. ¼ on S. face, from which the remains of the original bearing trees:</p> <p style="margin-left: 40px;">A hemlock, 21 ins. diam., bears N. 19° E., 7½ lks. dist., with healed blaze. (Record, 6 lks.)</p> <p style="margin-left: 40px;">A root hole, bears S. 73° E., 13 lks. dist., with a down cedar alongside, 30 ins. diam., no marks visible.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $\begin{array}{r} \text{T } 23 \text{ S } \text{ R } 8 \text{ W} \\ \frac{1}{4} \quad \frac{\text{S } 28}{\text{S } 33} \\ 1986 \end{array}$ </div> <p>from which a new bearing tree</p> <p style="margin-left: 40px;">A cedar, 48 ins. diam., bears S. 41° E., 26½ lks. dist., mkd. ¼ S33 BT.</p> <p>Deposit corner stone alongside iron post.</p> <p>From this point, United States Coast and Geodetic Survey triangulation station "OLD BLUE" bears S. 24° 13' 30" W., 135.685 chs. dist., monumented with a standard brass tablet, 3½ ins. diam., cemented in iron pipe, 4 ins. diam. firmly set, projecting 8 ins. above ground, with top mkd. OLD BLUE 1953 and a triangle.</p>	