

# County Surveyor's Record, Douglas County, Oregon

18291

Subdivision of Section 28,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
39.910	<p>N. 0° 01' 30" E., on the N. and S. center line of sec. 28.</p> <p>Ascend over gentle S. slope, through heavy timber and moderate undergrowth.</p> <p>Point for the center <math>\frac{1}{4}</math> sec. cor. of sec. 28, at intersection with the E and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 S R 8 W C <math>\frac{1}{4}</math> S 28 1986</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 21° W., 20 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 88<math>\frac{1}{2}</math>° W., 13<math>\frac{1}{2}</math> lks. dist., mkd. C <math>\frac{1}{4}</math> S28 BT.</p> <p>Continue ascent over gentle S. slope.</p>
57.05	<p>Waggoner Creek Road, 30 lks. wide, bears N. 85° W. and S. 85° E.; desc. over N. slope.</p>
59.955	<p>Point for the center N <math>\frac{1}{16}</math> sec. cor. of sec. 28.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N <math>\frac{1}{16}</math>   C 1986</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 31 ins. diam., bears N. 89<math>\frac{1}{2}</math>° E., 30 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 21<math>\frac{1}{2}</math>° W., 57 lks. dist., mkd. CN <math>\frac{1}{16}</math> S28 BT</p> <p>Continue descent over N. slope.</p>
67.90	<p>Creek, 5 lks. wide, course N. 50° E.; asc. over SE. slope.</p>
80.000	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 21 and 28.</p>
11.95	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 27 and 28.</p> <p>N. 89° 53' 30" W., on the E. and W. center line of sec. 28.</p> <p>Ascend over NE. slope, through logged area.</p> <p>Waggoner Creek Road, 30 lks. wide, bears S. 65° E. and West; desc. over broken SW. slope.</p>
19.930	<p>Point for the center E <math>\frac{1}{16}</math> sec. cor. of sec. 28.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C <math>\frac{E \frac{1}{16}}{S 28}</math> C 1986</p>