

County Surveyor's Record, Douglas County, Oregon

18292

Subdivision of Section 28,
T. 23 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	from which A fir, 13 ins. diam., bears S. 41° E., 38 lks dist., mkd CE 1/16 S28 BT. A fir, 9 ins. diam., bears N. 82° W., 20 lks. dist., mkd. X BT. Continue descent over broken SW. slope.
39.860	The center ¼ sec. cor. of sec. 28. Ascend over E. slope.
54.45	Gravelled road, 20 lks. wide, bears N. and N. 70° E. in a curve; desc. over W. slope.
59.860	Point for the center W 1/16 sec. cor. of sec. 28. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$C \quad \frac{W \ 1/16}{S \ 28} \quad C$ 1986
	from which A fir, 42 ins. diam., bears S. 32° W., 8 lks. dist., mkd. X BT. A fir, 38 ins. diam., bears N. 25° W., 32 lks. dist., mkd. CW 1/16 S28 BT. Continue descent over W. slope
79.860	The ¼ sec. cor. of secs. 28 and 29.
	From the center E 1/16 sec. cor. of sec. 28. N. 0° 09' 30" E., on the N. and S. center line of the NE ¼ of sec. 28. Ascend over SW. slope, through light timber and dense undergrowth.
6.10	Waggoner Creek Road, 20 lks. wide, bears N. 85° W. and S. 85° E.
8.95	Spur, slopes N. 60° W.; desc. over broken NW. slope.
19.985	Point for the NE 1/16 sec. cor. of sec. 28, at intersection with the E. and W. center line of the NE¼. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
10/2022 New CS 65/111-10	FO BC scribed steel. 2 6' tall slumps 1 New BT steel post <div style="text-align: center; margin-top: 10px;"> NE 1/16 S28 1986 </div>
	from which A fir, 17 ins diam., bears S. 78 ¾° E., 9 lks. dist., mkd. NE 1/16 S28 BT. A fir, 19 ins. diam., bears S. 19° W., 16 lks. dist., mkd. X BT. Continue descent over broken NW. slope.