

# County Surveyor's Record, Douglas County, Oregon

18293

Subdivision of Section 28,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
39.975	The E 1/16 sec. cor. of secs. 21 and 28.
	From the N 1/16 sec. cor. of secs. 27 and 28.
	N. 89° 44' 00" W., on the E. and W. center line of the NE 1/4 of sec. 28.
	Ascend over SE. slope, through logged area.
15.00	Gravelled road, 20 lks. wide, bears N. 50° E. and S. 30° W.; desc. over NW. slope, enter heavy timber.
19.965	The NE 1/16 sec. cor. of sec. 28.
	Continue descent over NW. slope.
39.945	The center N 1/16 sec. cor. of sec. 28.
	From the center W 1/16 sec. cor. of sec. 28,
	N. 0° 07' 30" E., on the N. and S. center line of the NW 1/4 of sec. 28.
	Descend over broken NW. slope, through heavy timber and moderate undergrowth.
19.95	Gravelled road, 15 lks wide, bears N. curving NW., and S curving SE., also, bottom of descent, slopes W.; asc. over SW. slope.
20.090	Point for the NW 1/16 sec. cor. of sec. 28, at intersection with the E. and W. center line of the NW 1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 32 ins. in the ground, the top 4 ins. below the surface of the road, with brass cap mkd.
	NW 1/16 S 28 1986
	from which
	A fir, 4 ins. diam., bears S. 88° E., 58 lks. dist., mkd. X BT.
	A fir, 9 ins. diam., bears N. 23 3/4° W., 167 lks. dist., mkd. NW 1/16 S28 BT.
	Continue ascent over SW. slope,
40.170	The W 1/16 sec. cor. of secs. 21 and 28.
	From the center N 1/16 sec. cor. of sec. 28.
	N. 89° 45' 00" W., on the E. and W. center line of the NW 1/4 of sec. 28.
	Descend over N. slope, through heavy timber and moderate undergrowth.
6.60	Creek, 2 lks. wide, course N. 35° E.; asc. over SE. slope.
8.40	Waggoner Creek Road, 28 lks. wide, bears N. 10° E. and S. 10° W.
10.25	Spur, slopes N. 20° E.; desc. over SW. slope.