

# County Surveyor's Record, Douglas County, Oregon

18296

T. 30 S., R. 9 W., Willamette Meridian, Oregon

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and the subdivision of section 17, Township 30 South, Range 9 West, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey and survey is as follows:

A portion of the subdivisional lines was surveyed by Dennis Hathor, U.S. Deputy Surveyor, in 1856.

The subdivisional lines were completed by William M. Bushey, U. S. Deputy Surveyor, in 1893.

A portion of the subdivisional lines was resurveyed by James E. Jelley, Cadastral Surveyor, in 1962.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the special Instructions dated March 17, 1982, for Group No. 1107, Oregon.

The directions of lines refer to the true meridian and were determined by exterior angles from direct solar observations.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified, and only the true line field notes are given herein. Only those lines bounding or crossing public lands were blazed. All lines not forming a closure were measured twice.

The geographic position of the  $\frac{1}{4}$  section corner of sections 16 and 17, as scaled from the U. S. Geological Survey's topographic map "BON Mountain", OREG.", 15 minute series 1954 edition, is as follows:

Latitude 42° 57.6' N. Longitude 123° 46.8' W.

The mean magnetic declination is 19° E.

Dependent Resurvey of  
a Portion of the Subdivisional Lines,  
T. 30 S., R. 9 W., Willamette Meridian, Oregon

(Restoring the survey by William M. Bushey in 1893,  
and the resurvey by James E. Jelley in 1962)

Beginning at the  $\frac{1}{4}$  sec. cor. of secs. 16 and 17, perpetuated and recorded by Jack E. LaFlamme, Registered Land Surveyor, No. 378, in 1979, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, in a mound of stone, 2½ ft. base, to top, with brass cap mkd.

G.P.  
 $\frac{1}{4}$  COR S 17 S 16  
T 30 S R 9 W  
1979