

County Surveyor's Record, Douglas County, Oregon

18298

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

26.80

Right bank of the Middle Fork of the coquille River, bears N. 60° E. and S. 60° W.; asc. 257 ft. over SE. slope.

29.70

Oregon State Highway No. 42, asphaltic surfaced, 50 lks. wide, bears N. 75° E. and S. 75° W.

40.18

The cor. of secs. 8, 9, 16, and 17, perpetuated and recorded by Vernon Tracy, Deputy Douglas County Surveyor, in 1964, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, and in mound of stone, 3 ft. base, to top, with brass cap mkd.

COUNTY SURVEYOR'S OFFICE

T 30S
S 8 | S 9
S 17 | S 16
R 9 W
1964

**Fd. Ok by K. DeGroot
1/2008 - M154-76**

from which the remains of the original bearing trees

A fir snag, 42 ins. diam., bears S. 50° W.,
116½ lks. dist., with fragmentary scribe marks
visible on an open blaze.

A white oak, 14½ ins. diam., bears N. 66 3/4° W.,
96 lks. dist., with a healed blaze.

and bearing trees mkd. by Tracy

A white oak, 15 ins. diam., bears N. 32° E.,
33 lks. dist., with a healed blaze.

A white oak, 9 ins. diam., bears S. 33° W.,
74 lks. dist., with a healed blaze.

A madrone, 12 ins. diam., bears N. 61° W.,
29 lks. dist., with fragmentary scribe marks
visible on a partially healed blaze.

From the ¼ sec. cor. of secs. 17 and 18, perpetuated and recorded by John M. Powell, Deputy Douglas County Surveyor, in 1965, from original evidence no longer in existence, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYOR'S OFFICE

T 30 S R 9 W
¼ S 18 | S 17
1965

from which bearing trees mkd. by Powell

A cedar, 10 ins. diam., bears S. 80° E., 70 lks.
dist., with fragmentary scribe marks visible
on a partially healed blaze.

A fir, 16 ins. diam., bears N. 32° W., 78 lks.
dist., with fragmentary scribe marks visible
on a partially healed blaze.

N. 0° 57' W., bet. secs. 17 and 18.