

County Surveyor's Record, Douglas County, Oregon

18300

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

A fir snag, 32 ins. diam., bears N. $48\frac{1}{4}^\circ$ W.,
30 $\frac{1}{2}$ lks. dist., with a healed blaze.

and bearing trees mkd. by Jelley in 1962

A cedar, 15 ins. diam., bears N. $27\frac{1}{2}^\circ$ E., 35 lks.
dist., with a healed blaze.

A cedar, 13 ins. diam., bears S. 38° E., 239 lks.
dist., with scribe marks T30S R9W S17 BT visible
on an open blaze.

A fir, 15 ins. diam., bears S. 57° W., 121 lks.
dist., with a healed blaze.

A fir, 34 ins. diam., bears N. 71° W., 87 lks.
dist., with a healed blaze.

and new bearing trees

A live oak, 4 ins. diam., bears S. 89° E., 32 lks.
dist., mkd. X BT.

A fir, 7 ins. diam., bears S. 5° W., 51 lks.
dist., mkd. X BT.

From the cor. of secs. 8, 9, 16, and 17.

N. $89^\circ 56'$ W., between secs. 8 and 17.

Ascend 120 ft. over broken SE. slope, through moderate
timber and undergrowth.

40.51

Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17, at proportionate
dist.,; there is no remaining evidence of the original cor.

Set an aluminum post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with aluminum cap mkd.

*FD OK BY D. EDWARDS
JUNE 2003 - M142-38*

T 30 S R 9 W
 $\frac{1}{4}$ $\frac{S 8}{S 17}$

*FD OK by K. DeGroot
1/2008 H154-74*

1982

from which:

A fir, 10 ins. diam., bears N. 9° E., 5 lks.
dist., mkd. $\frac{1}{4}$ S8 BT.

A cedar, 11 ins. diam., bears S. $66\frac{1}{2}^\circ$ E., $13\frac{1}{2}$ lks.
dist., mkd. $\frac{1}{4}$ S17 BT.

Ascend 224 ft. over broken SE. slope.

81.02

The cor. of secs. 7, 8, 17, and 18.

Subdivision of Section 17,
T. 30 S., R.9 W., Willamette Meridian, Oregon

From the $\frac{1}{4}$ sec. cor. of secs. 17 and 20, perpetuated and
recorded by Vernon Tracy, Deputy Douglas County Surveyor, in
1964, monumented with an iron post, 1 in. diam., firmly set
projecting 10 in. above ground, with brass cap mkd.