

# County Surveyor's Record, Douglas County, Oregon

18306

Dependent Resurvey of a Portion of the North Boundary,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

(Restoring the survey by Harvey Gordon and  
Charles T. Gardner, in 1855)

Beginning at the cor. of Tps. 21 and 22 S., Rs. 6 and 7 W., perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1960, and further perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1966, monumented with a "T" shaped iron rod, 1 in. diam., firmly set, projecting 3 ins. above ground, from which the remains of the original bearing trees:

A fir snag, 28 ins. diam., bears N. 59° E., 57 lks. dist., with fragmentary scribe marks visible on opened blaze.

A cedar, 38 ins. diam., bears S. 68° W., 14 lks. dist., with burned out face. (Record, 9 lks.)

and bearing trees mkd. by Tracy

A hemlock, 14 ins. diam., bears N. 80° E., 36 lks. dist., with healed blaze.

A cedar, 27 ins. diam., bears S. 59½° E., 45 lks. dist., with healed blaze.

A hemlock, 14 ins. diam., bears N. 27° W., 19 lks. dist., with healed blaze.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over "T" shaped iron rod, with brass cap mkd.

T 21 S
R 7 W   R 6 W
S 36   S 31
S 1   S 6
T 22 S
1986

Deposit a white "DEEP-1" magnetic marker at base  
of stainless steel post.

From this point, a reference point established and recorded by Vernon R. Tracy, deputy County Surveyor, in 1966, bears South, 0.008 chs. dist., monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 15 ins. above ground, with plastic cap mkd. DOUG. CO. SURVEYOR.

N. 89° 50' W., bet. secs. 1 and 36, marking and blazing the true line.

Descend over NW. slope, through ehavy timber and dense undergrowth.

4.00 Creek, 5 lks. wide, course N. 30° E.; asc. over broken SE. slope.

18.65 Spur, slopes N. 30° E.; desc. over NW. slope.

29.30 Dry creek, 5 lks. wide, course N. 40° E.; asc. over SE. slope.

38.59 Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.

*D. F. BAKER  
M 11A-26  
12/91*

T 21 S R 7 W
½ S 36
S 1
T 22 S
1986