

County Surveyor's Record, Douglas County, Oregon

18308 Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

(Restoring the survey by William H. Byars, in 1871)

From the cor. of secs. 1, 2, 11, and 12, perpetuated and recorded by Milo E. Godfrey, deputy County Surveyor, in 1962, monumented with an iron post, 1½ ins. diam., firmly set, projecting 9 ins. above ground (alongside is an iron pipe 1½ ins. diam., loosely set, projecting 27 ins. above ground), with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 22 S R 7 W
S 2 | S 1
S 11 | S 12
1962

from which original bearing trees

A cedar, 41 ins. diam., bears N. 60° E., 37 lks. dist., with partially healed blaze.

A fir, 50 ins. diam., bears S. 25° W., 15 lks. dist., with opened blaze.

and bearing trees mkd. by Godfrey

A white fir, 9 ins. diam., bears N. 76° E., 52 lks. dist., with healed double blaze.

A fir, 12 ins. diam., bears S. 39° E., 50 lks. dist., with healed double blaze.

A fir, 15 ins. diam., bears S. 85 3/4° W., 42 lks. dist., with healed double blaze.

A white fir, 26 ins. diam., bears N. 59 3/4° W., 65 lks. dist., with healed double blaze.

From this point, a point established and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1956, bears N. 76° 56' W., 0.055 chs. dist., monumented with a "T" shaped iron rod, 1 in. diam., firmly set, projecting 6 ins. above ground.

From this same point, the Douglas County Horizontal control Station "TOTEM", bears S. 48° 42' E., 88.62 chs. dist., monumented with a brass disk 3 ins. diam., set in concrete 12 ins. diam., flush with the ground, with top mkd. DOUGLAS CO SURVEYOR OFFICE, TOTEM 1982.

N. 2° 18' E., bet. secs. 1 and 2, marking and blazing the true line.

Ascend over gentle rolling S. slope, through heavy timber and dense undergrowth.

- 6.45 South edge of pond, bears N. 70° E. and N. 40° W.
- 7.70 North edge of pond, bears N. 75° E. and S. 30° W.
- 8.60 Dirt road, 18 lks. wide, bears N. 65° E. and S. 85° W.
- 10.24 Creek, 1 lk. wide, course S. 40° W.; asc. over gentle rolling S. slope.
- 19.55 Creek, 3 lks. wide, course S. 35° W.; asc. over gentle rolling S. slope.
- 22.55 Dirt road, 15 lks. wide, bears N. 55° W. and S. 65° E.
- 41.36 Point for the ½ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.