

County Surveyor's Record, Douglas County, Oregon

18312 Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 21 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

(Restoring the survey by Laban H. Wheeler, in 1883,
the survey by William P. Wright, in 1884, and the
resurvey by Floyd A. Brooks and James E. Jelley, in 1964)

Beginning at the cor. of secs. 13, 18, 19, and 24, on the E. bdy.
of the Tp., perpetuated and recorded by Milo E. Godfrey, Deputy
County Surveyor, in 1961, monumented with an iron post, 1½ ins.
diam., firmly set, projecting 15 ins. above ground, with brass
cap mkd.

COUNTY SURVEYOR OFFICE

T 21 S
S 13 | S 18
S 24 | S 19
R 7 W | R 6 W
1961

from which the remaining original bearing tree

A fir, 45 ins. diam., bears N. 13° E., 45 lks.
dist., with fragmentary scribe marks visible on
bark blaze. (Record, 56 lks.)

and the remains of bearing trees mkd. by Godfrey

A fir snag, size indeterminate, bears S. 25½° E.,
43 lks. dist., with healed double blaze.

A fir, 29 ins. diam., bears S. 29½° W., 87 lks.
dist., with healed blaze.

A fir, 38 ins. diam., bears S. 85° W., 90 lks.
dist., with healed double blaze.

No other suitable trees available.

Corner is located in logged area, on top of rock bluff, 20 ft.
high, on steep SE. slope.

From this point, United States Geological Survey triangulation
station "TOM FOLLEY 1953" bears S. 21° 08' 00" E., 239.835 chs.
dist., monumented with a brass tablet, 3 ins. diam., set in 3 in.
post, firmly set, projecting 2 ins. above ground, with top mkd.
US GEOLOGICAL SURVEY TOM FOLLEY 1953.

N. 88° 51' W., bet. secs. 13 and 24, marking and blazing the true
line.

Ascend over broken SE. slope, through ehavy timber and dense
undergrowth.

10.30 Spur, slopes S. 10° W.; desc. over SW. slope, changing to NW.
slope.

43.415 Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate
distance; there is no remaining evidence of the original corner.
Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T 21 S R 7 W
¼ S 13
S 24
1986

from which

A fir, 4 ins. diam., bears S. 5° W., 50 lks.
dist., mkd. X BT.