

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines **18313**
T 21 S., R. 7 W., Willamette Meridian, Oregon

CHAINS									
	<p style="margin-left: 40px;">A cedar, 37 ins. diam., bears N. 19° W., 72 lks. dist., mkd. ¼ S13 BT.</p> <p style="margin-left: 40px;">Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p style="margin-left: 40px;">Descend over NW. slope.</p>								
44.80	<p style="margin-left: 40px;">Creek bed, 15 lks. wide, drains S. 50° W.; asc. over broken SE. slope.</p>								
51.30	<p style="margin-left: 40px;">Spur, slopes S. 10° E.; desc. over broken SW. slope.</p>								
58.55	<p style="margin-left: 40px;">Ravine, drains S. 35° W.; asc. over broken SE. slope.</p>								
64.25	<p style="margin-left: 40px;">Spur, slopes S.; desc. over broken SW. slope.</p>								
74.05	<p style="margin-left: 40px;">Dirt road, 40 lks. wide, bears S. 25° W. and S. 20° E., in curve.</p>								
77.40	<p style="margin-left: 40px;">Same road, bears N. 70° W. and S. 55° E., in curve.</p>								
81.40	<p style="margin-left: 40px;">Same road, bears N. 40° E. and N. 80° W., in curve.</p>								
83.05	<p style="margin-left: 40px;">Same road, bears N. 20° E. and S. 15° W.</p>								
86.83	<p style="margin-left: 40px;">The cor. of secs. 13, 14, 23, and 24, perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1960, monumented with a 1 in. T shaped iron rod, firmly set, projecting 4 ins. above ground, from which the remains of an original bearing tree:</p> <p style="margin-left: 80px;">A fir snag, 22 ins. diam., bears S. 58° W., 34 lks. dist., no marks visible on opened blaze.</p> <p style="margin-left: 40px;">and a bearing tree mkd. by Haines</p> <p style="margin-left: 80px;">A fir, 52 ins. diam., bears N. 18° E., 40 lks. dist., with scribe marks T21S R7W S13 BT visible on bark blaze.</p> <p style="margin-left: 40px;">At the corner point</p> <p style="margin-left: 40px;">Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, directly over T iron, with brass cap mkd.</p> <div style="margin-left: 100px; text-align: center;"> <table style="border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 21 S R 7 W</td> <td style="padding: 0 10px;">FO. OK BY WARD 4/99</td> </tr> <tr> <td style="padding: 0 10px;">S 14 S 13</td> <td style="padding: 0 10px;">M 131-5A</td> </tr> <tr> <td style="padding: 0 10px;">S 23 S 24</td> <td></td> </tr> <tr> <td style="padding: 0 10px;">1986</td> <td></td> </tr> </table> </div> <p style="margin-left: 40px;">from which new bearing trees</p> <p style="margin-left: 80px;">A fir, 8 ins. diam., bears S. 73° E., 67 lks. dist., mkd. T21S R7W S24 BT.</p> <p style="margin-left: 80px;">A fir, 6 ins. diam., bears N. 85° W., 44 lks. dist., mkd. T21S R7W S14 BT.</p> <p style="margin-left: 40px;">No other suitable trees available.</p> <p style="margin-left: 40px;">Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p style="margin-left: 40px;">Land, mountainous. Soil, rocky clay loam. Timber, fir, cedar, alder, and maple; undergrowth, vine maple, huckleberry, salmonberry, salal, Oregon grape, ferns, and grass.</p>	T 21 S R 7 W	FO. OK BY WARD 4/99	S 14 S 13	M 131-5A	S 23 S 24		1986	
T 21 S R 7 W	FO. OK BY WARD 4/99								
S 14 S 13	M 131-5A								
S 23 S 24									
1986									