

County Surveyor's Record, Douglas County, Oregon

18314 Dependent Resurvey of a Portion of the Subdivisional Lines,
T 21 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p>From the cor. of secs. 27, 28, 33, and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above ground, alongside of which is lying a T iron, 36 ins. long, 1 in. diam., The brass cap is mkd.</p>
	<p>T 21 S R 7 W S 28 S 27 S 33 S 34 1964</p>
	<p>From which the remaining original bearing tree</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears N. 40° E., 33 lks. dist., with healed blaze.</p> <p>and bearing trees mkd. by W. N. Haines, Registered Land Surveyor No. 239, in 1961.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 13° W., 4½ lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 66½° W., 8 lks. dist., with healed blaze.</p> <p>and a bearing tree mkd. by Brooks and Jelley</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 23° E., 42 lks. dist., with healed blaze. (Record, S. 26½° E., 43½ lks.)</p> <p>N. 0° 23' E., bet. secs. 27 and 28.</p> <p>Ascend over SE. slope, along W. edge of timber, through dense undergrowth.</p>
0.35	Spur, slopes N. 70° E.; desc. over NE. slope.
3.90	Ravine, drains N. 80° E.; asc. SE. slope.
11.20	Spur, slopes N. 65° E.; desc. over NW. slope.
21.30	Ravine, drains E.; asc. SE. slope.
32.85	Saddle in spur, bears N. 55° E. and S. 55° W.; desc. over NW. slope.
37.265	<p>Point for the ¼ sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap.</p>
	<p>T 21 S R 7 W ¼ S 28 S 27 1986</p>
	<p>from which</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 68° E., 57 lks. dist., mkd. ¼ S27 BT.</p> <p style="padding-left: 40px;">A hemlock, 8 ins. diam., bears N. 36½° W., 53½ lks. dist., mkd. ¼ S28 BT.</p> <p style="padding-left: 40px;">Deposit white "DEEP-1" magnetic marker at base of iron post.</p> <p>From this point, a point of no known record, bears S. 19° 07' E., 0.106 chs. dist., monumented with an iron rod, 1¼ ins. diam., firmly set, projecting 12 ins. above ground.</p>