

County Surveyor's Record, Douglas County, Oregon

18315

Dependent Resurvey of a Portion of the Subdivisional Lines,
T 21 S., R. 7 W., Willamette Meridian, Oregon.

CHAINS																	
	Descend over NW. slope, changing to NE. slope.																
45.90	Creek, 4 lks. wide, course N. 80° E.; asc. over broken SE. slope.																
57.60	Leave logged area, edge bears NW. and S., and enter timber.																
64.40	Spur, slopes N. 45° E.; desc. over NE. slope.																
73.40	Creek, 1 lk. wide, course N. 75° E.; asc. over SE. slope.																
74.53	The cor. of secs. 21, 22, 27, and 28, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, alongside of which is a 1 in. T shaped iron rod, firmly set, projecting 8 ins. above ground. The brass cap is mkd.																
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="4">T 21 S R 7 W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 21</td> <td style="border-right: 1px solid black; padding: 0 5px;">S 22</td> <td colspan="2"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 28</td> <td style="border-right: 1px solid black; padding: 0 5px;">S 27</td> <td colspan="2"></td> </tr> <tr> <td colspan="4" style="text-align: center;">1964</td> </tr> </table>	T 21 S R 7 W				S 21	S 22			S 28	S 27			1964			
T 21 S R 7 W																	
S 21	S 22																
S 28	S 27																
1964																	
	from which the remains of the original bearing trees																
	A fir, 72 ins. diam., bears N. 80° E., 53 lks. dist., with healed blaze.																
	A sawed fir stump, 52 ins. diam., bears S. 10° W., 34 lks. dist., with healed blaze.																
	A fir, 58 ins. diam., bears N. 52° W., 13 lks. dist., with healed blaze and scribe marks BT S21 T21S R7W visible on bark.																
	and the remains of bearing trees mkd. by Brooks and Jelley																
	A hemlock, 19 ins. diam., bears N. 68 ¾° E., 48 lks. dist., with healed blaze.																
	A sawed cedar stump, 28 ins. diam., bears S. 27° E., 93 lks. dist., with scribe marks S R7W visible on partially healed blaze. (Record, S. 28° E.)																
	A cedar, 43 ins. diam., bears N. 28° W., 57 lks. dist., with scribe marks T21S R7W S21 BT visible on partially healed blaze. (Record, 79 lks.)																
	and a new bearing tree																
	A maple, 13 ins. diam., bears S. 44° W., 76½ lks. dist., mkd. T21S R7W S28 BT.																
	Land, mountainous. Soil, rocky clay loam. Timber, fir, cedar, hemlock, alder, and maple; undergrowth, vine maple, huckleberry, salmonberry, salal, Oregon grape, arrowwood, ferns, and grass.																
	From the cor. of secs. 27, 28, 33, and 34.																
	S. 88° 43' W., bet. secs. 28 and 33.																
	Ascend over SE. slope, changing to NE. slope, along N. edge of timber.																
6.95	Ridge, bears N. 25° W. and S. 25° E.; desc. over broken SW. slope.																
40.31	The ¼ sec. cor. of secs. 28 and 33, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.																