

County Surveyor's Record, Douglas County, Oregon

18316 Dependent Resurvey of a Portion of the Subdivisional Lines
T 21 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	T 21 S R 7 W $\frac{1}{4}$ S 28 $\frac{1}{4}$ S 33 1964
	from which the remaining bearing tree mkd. by Brooks and Jelley A white fir, 12 ins. diam., bears N. 54° E., 14 lks. dist., with healed blaze. and a new bearing tree A fir, 6 ins. diam., bears S. 38½° E., 34½ lks. dist., mkd. $\frac{1}{4}$ S33 BT. From this point, United States Geological Survey triangulation station "TOM FOLLEY 1953", bears S. 79° 03' 00" E., 370.130 chs dist., hereinbefore described. Land, mountainous. Soil, rocky clay loam. Timber, fir, cedar, alder, maple, and hemlock; undergrowth, vine maple, huckleberry, salmonberry, Oregon grape, salal, fern, and grass.
	Subdivision of Section 28, T. 21 S., R. 7 W., Willamette Meridian, Oregon
	From the $\frac{1}{4}$ sec. cor. of secs. 28 and 33. N. 1° 49' E., on the N. and S. center line of sec. 28, marking and blazing the true line. Ascend over SW. slope, through heavy timber and dense undergrowth
32.80	Gravelled road, 20 lks. wide, bears N. 60° W. and S. 50° E.; also ridge, bears N. 45° W. and S. 65° E.; desc. over NE. slope. Enter logged area, edge bears N. 45° W. and S. 65° E.
36.40	Ravine, drains N. 70° E.; asc. over SE. slope.
37.85	Point for the center $\frac{1}{4}$ sec. cor. of sec. 28, at intersection with the E. and W. center line. Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.
	T 21 S R 7 W C $\frac{1}{4}$ S 28 1986
	from which A fir, 5 ins. diam., bears S. 34° W., 138½ lks. dist., mkd. C $\frac{1}{4}$ S28 BT. A fir, 50 ins. diam., bears N. 12° W., 19 lks. dist., mkd. C $\frac{1}{4}$ S28 BT. From this point, a point of no known record, bears S. 60° 30' W. 0.093 chs. dist., monumented with an iron rod, 1½ ins. diam., firmly set, projecting 6 ins. above ground Ascend over SE. slope, also leave logged area, edge bears E. and W., enter timber.