

# County Surveyor's Record, Douglas County, Oregon

**18322**

Dependent Resurvey of a Portion of the South Boundary,  
T. 30 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
	<p>A madrone, 14 ins.diam., bears S. 16½° W., 41 lks. dist. with partially healed blaze and fragmentary scribe marks visible on bark.</p> <p>A madrone, 9 ins. diam., bears N. 58° W., 29 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p>
2.06	<p>N. 89° 38' W., on the S. bdy. of sec. 31.</p> <p>Ascend over E. slope, through heavy timber and dense undergrowth.</p> <p>The ¼ sec. cor. of sec. 6 only, T. 31 S., R. 3 W., established and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1960, perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1966, and is accepted as the corner, monumented with an iron pipe, 1½ ins.diam., firmly set, projecting 16 ins. above ground, alongside is an iron post, 1½ ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T30S ¼ S6 T31S R3W 1966, from which bearing trees mkd.by Markham:</p> <p style="padding-left: 40px;">A chinkapin, 12 ins.diam.,bears N. 17½° E., 31 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A chinkapin, 10 ins. diam., bears S. 74¼° E., 39 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam.,bears S. 43° E., 36 lks. dist., with healed blaze.</p>
10.40	<p>S. 89° 43' W., beginning new measurement.</p> <p>Ascend over broken E. slope, through young timber and dense undergrowth.</p> <p>Ridge, bears N. 32° E. and S. 32° W.; desc. over steep, broken NW. slope.</p>
31.45	<p>Ravine, crains N. 52° W.; asc. over NE. slope.</p>
35.50	<p>Spur, slopes N. 70° W.; desc. over SW.slope.</p>
36.40	<p>The ¼ sec. cor. of sec. 31 only, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with the original stone, firmly set, projecting 2 ins. above ground, mkd. ¼ on N. face, alongside is an iron post, 1¼ ins. diam., firmly set, projecting 12 ins. above ground,with brass cap mkd. COUNTY SURVEYORS OFFICE T30S ¼ SOUTH S31 R3W T31S 1963, from which the original bearing trees:</p> <p style="padding-left: 40px;">A fir, 16 ins. diam.,bears N. 56½° E., 14½ lks. lks. with healed blaze.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 57 3/4° W., 27½ lks. dist. with healed blaze.</p>
<p>Dependent Resurvey of a Portion of the Subdivisional Lines T. 31 S., R. 3 W., Willamette Meridian, Oregon</p>	
<p>(Restoring the survey by William H. Byars, in 1871, and the retracement and survey by William M. Bushey, in 1893-94)</p>	