

# County Surveyor's Record, Douglas County, Oregon

18323

Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 31 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

From the cor. of secs. 27, 28, 33 and 34, perpetuated and recorded by George J. Wenderoth, Deputy County Surveyor, in 1946 perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1966, and perpetuated by Glen S. Baughman, Registered Land Surveyor No. 536, in 1979, monumented with an iron post, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 31 S R 3 W

S 28 | S 27

S 33 | S 34

1966

from which the original bearing trees

A madrone, 30 ins. diam., bears S. 10° E., 35 lks. dist., with a rotted center. (Record, 32 lks.)

A fir, 18 ins. diam., bears S. 35° W., 26 lks. dist., with healed blaze.

and the remains of the bearing trees mkd. by Bushey

A pine stump, 34 ins. diam., bears N. 15° E., 96 lks. dist., with healed blaze. (Record, 93½ lks.)

A madrone stump, 25 ins. diam., bears N. 49° W., 77 lks. dist., with scribe marks R3 S28 visible on an opened blaze. (Record, 78½ lks.)

and a bearing tree mkd. by Wenderoth

A madrone, 22 ins. diam., bears S. 24½° E., 61 lks. dist. with scribe marks S 4 B visible on a partially healed double blaze.

and bearing trees mkd. by Baughman

A fir, 14 ins. diam., bears N. 41° E., 185 lks. with two healed blazes.

A fir, 9 ins. diam., bears N. 10½° W., 103 lks. dist. with scribe marks T31S R3W S28 BT visible on a partially healed blaze and with a brass washer marked LS 536 nailed to a lower blaze.

N. 1° 23' E., bet. secs. 27 and 28.

Ascend over a broken SE. slope, through heavy timber and dense undergrowth.

5.60 Gravel road, 50 lks. wide, bears N. 50° E. and S. 50° W.

19.69 The S 1/16 sec. cor. of secs. 27 and 28, established and recorded by William J. Ruppert, Registered Land Surveyor No. 866, in 1980, and is accepted as the corner, monumented with an aluminum post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with a mound of stone, 4 ft. base, to top, with aluminum cap mkd.

T 31 S R 3 W

S 1/16

S 28 | S 27

PLS 866

1980

from which bearing trees mkd. by Ruppert