

County Surveyor's Record, Douglas County, Oregon

18325

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 31 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend over broken NE. slope.</p>
40.56	<p>The cor. of secs. 21, 22, 27, 28, perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1966, monumented with an iron post, 1½ ins. diam., firmly set, projecting 10 ins. above ground, (with the original sandstone, 14 x 10 x 8 ins., lying alongside, with 2 notches on the S. edge and 3 notches on the E. edge), with brass cap mkd.</p> <p style="text-align: center;"> COUNTY SURVEYORS OFFICE T 31 S R 3 W S 21 S 22 S 28 S 27 1966 </p> <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A fir snag, 8 ins. diam., bears N. 23½° E., 22 lks. dist., with scribe marks T31S R3W S22 BT visible on an opened blaze.</p> <p style="margin-left: 40px;">A root hole, bears S. 45½° E., 34¼ lks. dist., with a rotted fir, 22 ins. diam., lying alongside, no marks remaining.</p> <p style="margin-left: 40px;">A madrone, 25 ins. diam., bears S. 80½° W., 29 lks. dist., with a rotted blaze.</p> <p style="margin-left: 40px;">A fir, 26 ins. diam., bears N. 85° W., 46 lks. dist., with healed blaze.</p> <p>and a bearing tree mkd. by Powell</p> <p style="margin-left: 40px;">A fir, 15 ins. diam., bears N. 33½° E., 31 lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p style="margin-left: 40px;">A fir, 4 ins. diam., bears S. 28° E., 23½ lks. dist., marked X BT.</p>
	<p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>S. 88° 45' W., bet. secs. 28 and 33.</p> <p>Ascend over E. slope, through heavy timber and dense undergrowth.</p>
2.10	<p>Gravel road, 30 lks. wide, bears N. 20° E. and S. 20° W.</p>
5.30	<p>Spur, slopes S.; desc. over SW. slope.</p>
9.20	<p>Gravel road, 30 lks. wide, bears N. 80° W. and S. 80° E.</p>
13.20	<p>Ravine, drains S.; asc. over a SE. slope.</p>
16.40	<p>The E 1/16 sec. cor. of sec. 28 only, established and recorded by William J. Ruppert, Registered Land Surveyor No. 866, in 1980, and is accepted as the corner, monumented with an aluminum post. 2 ins. diam., set flush with the top of a mound of stone, 3 ft. base, 6 ins. high, with an aluminum cap mkd.</p> <p style="text-align: center;"> T 31 S R 3 W ONLY E 1/16 S 28 PLS 866 1980 </p> <p>from which bearing trees mkd. by Ruppert</p>