

County Surveyor's Record, Douglas County, Oregon

18326 Dependent Resurvey of a Portion of the Subdivisional Lines
T. 31 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 14 ins. diam., bears N. $38\frac{1}{2}^{\circ}$ E., 73 lks. dist. with healed blaze.</p> <p>A fir, 33 ins. diam., bears N. $75\frac{3}{4}^{\circ}$ E., 41 lks. dist. with scribe marks E 1/16 S28 visible on a partially healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. $88^{\circ} 45'$ W., beginning a new measurement.</p> <p>Ascend over SE. slope.</p>
1.20	Gravel road, 30 lks. wide, bears NE. and SW.
3.00	Same road, bears N. 20° E. and S. 20° W.
18.70	Ridge, bears N. 30° E and S. 30° W.; desc. over broken W. slope.
20.40	<p>The $\frac{1}{4}$ sec. cor. of sec. 28 only, established and recorded by William J. Ruppert, Registered Land Surveyor No. 866, in 1980, and is accepted as the corner, monumented with an aluminum post, 2 ins. diam., projecting 8 ins. above the ground, with a mound of stone, 3 ft. base, to top, with an aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 31 S R 3 W ONLY <u>$\frac{1}{4}$ S 28</u> PLS 866 1980</p> </div> <p>from which bearing trees mkd. by Ruppert</p> <p>A fir, 9 ins. diam., bears N. 75° E., 33 lks. dist., with scribe marks S28 visible on a partially healed blaze.</p> <p>A fir, 8 ins. diam., bears N. 44° W., 6 lks. dist., with scribe mark 8 visible on a partially healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. $88^{\circ} 45'$ W., beginning a new measurement.</p> <p>Descend over a steep W. slope.</p>
2.30	<p>The $\frac{1}{4}$ sec. cor. of sec. 33 only, perpetuated and recorded by William J. Ruppert, Registered Land Surveyor No. 866, in 1980, monumented with an aluminum post, 2 ins. diam., firmly set, projecting 10 ins. above ground, in a mound of stone, 3 ft. base, to top, with an aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 31 S R 3 W <u>$\frac{1}{4}$ S 33 ONLY</u> PLS 866 1980</p> </div> <p>from which the remains of a bearing tree mkd. by Bushey</p> <p>A fir stump, 40 ins. diam., bears N. $47\frac{1}{2}^{\circ}$ E., 72 lks. dist., with scribe marks $\frac{1}{4}$ visible on an opened blaze.</p> <p>and the bearing trees mkd. by Ruppert</p> <p>A fir, 20 ins. diam., bears S. 14° E., 113 lks. dist., with healed blaze.</p> <p>A fir, 9 ins. diam., bears S. 46° W., $12\frac{1}{2}$ lks. dist., with illegible scribe marks visible on a partially healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/>