

County Surveyor's Record, Douglas County, Oregon

18327

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 31 S., R. 3 W., Willamette Meridian, Oregon

CHAINS					
	S. 89° 28' W., beginning new measurement				
	Descend over broken W. slope.				
38.50	<p>The cor. of secs. 28, 29, 32, and 33, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1960, further perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1964, and by John M. Powell, deputy County Surveyor, in 1966, monumented with an iron post, 1½ ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEYORS OFFICE</p> <p>T 31 S R 3 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 29</td> <td style="padding: 0 5px;">S 28</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 32</td> <td style="padding: 0 5px;">S 33</td> </tr> </table> <p>1966</p> </div> <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A fir stump, 22 ins.diam., bears N. 45° E., 37 lks. dist., with healed blaze. (Record, N. 50° E.)</p> <p style="margin-left: 40px;">A root hole, bears S. 60° E., 51 lks. dist., with a tipped out fir stump, 40 ins. diam., lying alongside, with healed blaze.</p> <p style="margin-left: 40px;">A fir, 15 ins. diam., bears S. 30° W., 22 lks. dist., with healed blaze.</p> <p>and the remains of the bearing trees mkd. by Byron</p> <p style="margin-left: 40px;">A root hole, bears N. 85° E., 38 lks.dist., with a fir, 20 ins. diam., lying alongside, with scribe marks T31S R3W S28 CS BT visible on an open blaze.</p> <p style="margin-left: 40px;">A fir, 22 ins. diam., bears S. 3° E., 19 lks. dist. with a healed blaze.</p> <p style="margin-left: 40px;">A fir stump, 18 ins. diam., bears N. 54° W., 42 lks. dist. with scribe marks T31S R3W S29 CS BT visible on an open blaze.</p> <p>and bearing trees mkd. by Godfrey</p> <p style="margin-left: 40px;">A fir, 16 ins. diam., bears N. 25° E., 50 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A fir, 18 ins. diam., bears N. 71° W., 70 lks. dist., with healed blaze.</p> <p>The corner is 10 lks. N. of the Bottom of a ravine draining W.</p>	S 29	S 28	S 32	S 33
S 29	S 28				
S 32	S 33				
	N. 0° 06' E., bet. secs. 28 and 29.				
	Ascend over a broken SW. slope, through scattering timber and dense undergrowth.				
1.70	Top of ascent, slopes W.; desc. over a broken NW. slope.				
13.40	Dirt road, 30 lks. wide, bears N. 30° E. and S. 30° W.				
17.40	Creek, 3 lks. wide, course S. 70° W.; asc. over a broken SE. slope.				
40.48	The ¼ sec. cor. of secs. 28 and 29, perpetuated and recorded by James W. Byron, Deputy County Suraveyor, in 1960, and further perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1966, monumented with an iron post, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.				