

# County Surveyor's Record, Douglas County, Oregon

18329

Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 31 S., R. 3 W., Willamette Meridian, Oregon

CHAINS							
	<p>A madrone, 30 ins. diam., bears S. 18½° W., 29½ lks. dist., with healed blaze.</p> <p>A cedar snag, 37 ins. diam., bears N. 48 3/4° W., 47 lks. dist., with illegible scribe marks visible on an opened blaze. (Record, 45 lks.)</p> <p>and the remains of the bearing trees mkd. by Godfrey</p> <p>A fir, 20 ins. diam., bears N. 12° E., 17 lks. with healed blaze.</p> <p>A fir stump, 18 ins. diam., bears S. 77° E., 48 lks. dist., with scribe mark T visible on an open blaze.</p> <p>A fir, 15 ins. diam., bears N. 7° W., 16 lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 8 ins. diam., bears S. 58° E., 17 lks. dist., mkd. T31S R3W S28 BT.</p>						
	<p>From the cor. of secs. 21, 22, 27, 28.</p> <p>N. 89° 51' W., bet. secs. 21 and 28.</p> <p>Ascend over an E. slope, through heavy timber and dense undergrowth.</p>						
1.75	Ridge, bears NE. and SW.; desc. over broken NW. slope						
15.90	Abandoned dirt road, 30 lks. wide, bears N. 40° E. and S. 40° W.						
17.23	<p>Point for the E 1/16 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr> <td style="padding: 0 10px;">E 1/16</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 21</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding: 0 5px;">S 28</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding: 0 5px;">1986</td> </tr> </table> </div> <p>from which</p> <p>A fir, 9 ins. diam., bears S. 57° E., 26 lks. dist., mkd. E 1/16 S28 BT.</p> <p>A fir, 6 ins. diam., bears N. 75° W., 11 lks. dist., mkd. E 1/16 S21 BT.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Continue over broken NW. slope.</p>	E 1/16	S 21		S 28		1986
E 1/16	S 21						
	S 28						
	1986						
27.40	Creek, 1 lk. wide, course N. 15° W.; asc. over broken NE. slope.						
30.20	Spur, slopes N.; desc. over NW. slope.						
32.40	Creek, 6 lks. wide, course NE.; asc. over broken E. slope.						
38.56	<p>The ¼ sec. cor. of secs. 21 and 28, perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1966, monumented with an iron post, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p>						