

# County Surveyor's Record, Douglas County, Oregon

**18330**    Dependent Resurvey of a Portion of the Subdivisional Lines  
                   T. 31 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

T 31 S R 3 W

$\frac{1}{4}$   $\frac{S 21}{S 28}$

1966

from which the original bearing trees

A madrone, 20 ins. diam., bears N. 41° E., 24½ lks. dist.  
with a rotted blaze.

A madrone, 20 ins. diam., bears S. 9½° W., 36 lks. dist.,  
with healed blaze. (Record, 34 ¾ lks.)

and bearing trees mkd. by Powell

A fir, 12 ins. diam., bears N. 10° E., 72 lks. dist.,  
with healed blaze.

A fir, 10 ins. diam., bears S. 40° E., 28 lks. dist.,  
with a healed blaze.

\_\_\_\_\_

S. 89° 52' W., beginning new measurement.

Ascend over a steep E. slope.

6.90    Dirt road, 15 lks. wide, bears N. 25° E. and S. 40° W.

7.60    Spur, slopes N. 20° E.; desc. over a broken NW. slope.

14.40    Creek, 1 lk. wide, course N. 10° W.; asc. over NE. slope.

16.90    Spur, slopes N.; desc. over NW. slope.

19.865    Point for the W 1/16 sec. cor. of secs. 21 and 28, is located in  
a creek, 2 lks. wide, course N. 20° E., where it is impracticable  
to establish a permanent monument.

20.195    Point selected for a witness corner to the W 1/16 sec. cor. of  
secs. 21 and 28.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins.  
in the ground, with brass cap mkd.

                  WC  
W 1/16  $\frac{S 21}{S 28}$  →  
                  1986

from which

A hemlock, 8 ins. diam., bears N. 30° E., 5 lks. dist.  
mkd. X at breast height and BT at the base.

A hemlock, 4 ins. diam., bears S. 10° E., 21 lks. dist.,  
mkd. X at breast height and BT at the base.

Deposit white "DEEP-1" magnetic marker at base of  
stainless steel post.

Ascend over NE. slope.

27.30    Top of ascent, slopes N.; desc. over NW. slope.

28.50    Creek, 2 lks. wide, course N. 15° E.; asc. over a NE. slope.

39.73    The cor. of secs. 20, 21, 28 and 29.