

# County Surveyor's Record, Douglas County, Oregon

18331

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 31 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
	N. 0° 15' E., bet. secs. 20 and 21.
	Descend over broken N. slope, through heavy timber and dense undergrowth.
1.05	An original line tree, a fir, 30 ins. diam., with faint hack marks in the bark on the N. and S. sides.
	<hr style="width: 20%; margin: 0 auto;"/>
	N. 0° 15' E., beginning new measurement.
10.05	Ravine, drains N. 75° E.; asc. over a SE. slope.
11.25	Spur, slopes N. 30° E.; desc. over NW. slope.
28.95	Creek, 3 lks. wide, course N. 75° E.; asc. over a broken SE. slope.
31.45	Spur, slopes N. 60° E.; desc. over NW. slope.
32.35	South edge of swamp, bears N. 70° E. and S. 70° W.
33.65	North edge of swamp, bears S. 50° E. and S. 75° W.; asc. over broken SW. slope.
37.15	Top of ascent, slopes S. 40° E.; desc. over NE. slope.
39.16	The $\frac{1}{4}$ sec. cor. of secs. 20 and 21, perpetuated and recorded by Norman D. Price, Registered Land Surveyor No. 33, in 1955 monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 8 ins. above ground, with a brass disk mkd. LS 33 and with the original basalt stone, 12 x 10 x 6 ins., mkd. $\frac{1}{4}$ , lying alongside, from which the remains of the original bearing trees: <ul style="list-style-type: none"> <li>A root hole, bears S. <math>54\frac{1}{2}^\circ</math> E., <math>44\frac{1}{2}</math> lks. dist., with a burnt hemlock stump lying alongside, size indeterminate no remaining marks.</li> <li>A root hole, bears S. <math>74\frac{1}{2}^\circ</math> W., <math>30\frac{3}{4}</math> lks. dist., with a burnt yew, alongside, size indeterminate, no remaining marks.</li> </ul> and bearing trees mkd. by Price <ul style="list-style-type: none"> <li>A hemlock, 23 ins. diam., bears S. <math>70\frac{1}{2}^\circ</math> E., 61 lks. dist. with illegible scribe marks on an opened blaze.</li> <li>A yew, 17 ins. diam., bears N. <math>88^\circ</math> W., 75 lks. dist., with scribe marks <math>\frac{1}{4}</math> S20 RS 33 BT on an open blaze.</li> </ul> At the corner point <p style="margin-left: 2em;">Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-left: 2em;"> <p>T 31 S R 3 W</p> <p style="margin-left: 4em;"><math>\frac{1}{4}</math></p> <p style="margin-left: 4em;">S 20   S 21</p> <p style="margin-left: 4em;">1986</p> </div> Deposit the iron post and the original stone alongside and a white "DEEP-1" magnetic marker at base of stainless steel post. <hr style="width: 20%; margin: 1em auto;"/>
	N. 0° 13' W., beginning new measurement.
	Descend over NE. slope.
1.30	Creek, 1lk. wide, course SE.; asc. over broken SE. slope.