

# County Surveyor's Record, Douglas County, Oregon

**18332** Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 31 S., R. 3 W., Willamette Meridian, Oregon

**CHAINS**

20.31

The N 1/16 sec. cor. of secs. 20 and 21, established and recorded by Howard W. Johnstone, Registered Land Surveyor No. 498, in 1985, and is accepted as the corner, monumented with a steel rod, ½ in. diam., projecting 8 ins. above ground, with an aluminum cap mkd. T31S R3W N 1/16 20 21 1985 LS 498, from which bearing trees mkd. by Johnstone:

A fir, 5 ins. diam., bears N. 30° E., 35 lks. dist., with scribe marks N 1/16 BT visible on a partially healed blaze, and with a brass disk nailed to the blaze, mkd. RLS 498.

A fir, 5 ins. diam., bears S. 81° W., 9½ lks. dist., with scribe marks N 1/16 BT visible on a partially healed blaze, and with a brass disk nailed to the blaze, mkd. RLS 489.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 32 ins. in the ground, the top 4 ins. below surface of dirt road, with brass cap mkd.

N 1/16  
S 20 | S 21  
1986

Deposit the steel rod alongside and a white "DEEP-1" magnetic marker at base of stainless steel post.

The corner is located in the westerly track of an abandoned dirt road, 15 lks. wide, bearing N. 10° E. and S. 10° W.

N. 0° 13' W., beginning new measurement.

Ascend over SE. slope.

2.40

Spur, slopes E.; desc. over broken NE. slope.

5.40

Dirt road, 15 lks. wide, bears N. 40° E. and S. 40° W.

11.10

Ravine, drains E.; asc. over SE. slope.

15.40

Dirt road, 15 lks. wide, bears NE. and SW.

20.31

The cor. of secs. 16, 17, 20, and 21, perpetuated and recorded by John H. Markham Jr., Registered Engineer No. 2880, in 1959, monumented with an iron pipe, 1¼ ins. diam., projecting 12 ins. above ground, with the original basalt stone, 15 x 11 x 6 ins., (record, 20 x 12 x 10 ins.), set alongside, with 4 notches on the E. and 3 notches on the S. faces, from which the remains of the original bearing trees:

A fir, 42 ins. diam., bears N. 44° E., 55 lks. dist., with healed blaze.

A fir, 42 ins. diam., bears S. 75½° E., 83 lks. dist., with healed blaze. (Record, 81 ¾ lks.)

A fir stump, 46 ins. diam., bears S. 11° W., 20½ lks. dist., with healed blaze.

A madrone, 13 ins. diam., bears N. 69¼° W., 28 lks. dist., with a rotted out blaze.

and bearing trees mkd. by Markham

A cedar, 17 ins. diam., bears N. 12° E., 58½ lks. dist., with two healed blazes.