

# County Surveyor's Record, Douglas County, Oregon

18333

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 31 S., R. 3 W., Willamette Meridian, Oregon.

CHAINS	
	<p>A cedar, 15 ins. diam., bears S. 79° E., 13 lks. dist., with healed blaze.</p> <p>A madrone, 15 ins. diam., bears S. 59° W., 6 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 31 S R 3 W S 17   S 16 S 20   S 21 1986</p> <p>Deposit the original stone and iron pipe alongside and white "DEEP-1" magnetic marker at base of stainless steel post.</p>
	<p>From the cor. of secs. 5, 6, 7, and 8, perpetuated and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1960, further perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1966, monumented with an iron axle, 1 in. diam., flange up, firmly set, projecting 12 ins. above ground, alongside is an iron post, 1½ ins. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T31S R3W S5 S6 S7 S8 1966, from which the remaining original bearing trees:</p> <p>A fir, 32 ins. diam., bears N. 6° E., 92 lks. dist., with healed blaze.</p> <p>A fir, 37 ins. diam., bears S. 37° W., 122 lks. dist., with healed blaze.</p> <p>A fir, 24 ins. diam., bears N. 40½° W., 40½ lks. dist., with healed blaze.</p> <p>and the remains of bearing trees mkd. by Markham</p> <p>A fir stump, 7 ins. diam., bears N. 48 ¾° E., 8 lks. dist., with scribe marks S5 BT visible on partially healed blaze</p> <p>A fir, 6 ins. diam., bears S. 45 ¾° E., 10 lks. dist., with healed blaze.</p> <p>A fir, 24 ins. diam., bears S. 19½° W., 13 lks. dist., with healed blaze.</p> <p>A fir, 20 ins. diam., bears N. 86½° W., 40 lks. dist., with healed blaze.</p> <p>S. 89° 25' W., bet. secs. 6 and 7.</p> <p>Descend over broken SW. slope, changing to W. slope, through moderate timber and undergrowth.</p>
1.00	Dirt road, 15 lks. wide, bears N. 50° E. and S. 50° W.
4.65	Slope changes to steep broken NW. slope.
19.90	Point for the E 1/16 sec. cor. of secs. 6 and 7.
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">E 1/16    S 6           S 7           1986</p>