

County Surveyor's Record, Douglas County, Oregon

18334 Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 31 S., R. 3 W., Willamette Meridian, Oregon

CHAINS					
	<p>from which</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears S. 39° W., 38 lks. dist., mkd. E 1/16 S7 BT.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 67° W., 66½ lks. dist., mkd. E 1/16 S6 BT.</p> <p style="padding-left: 40px;">Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend over broken W. slope.</p>				
24.45	Ravine, drains N. 20° W.; asc. over NE. slope.				
26.75	Spur, slopes N. 10° E.; desc. over broken W. slope.				
29.55	East Fork Poole Creek, 9 lks. wide, course N. 50° E.; asc. over broken SE. slope.				
37.95	Ravine, drains S. 80° E.; continue ascent over broken SE. slope.				
39.80	The ¼ sec. cor. of secs. 6 and 7, perpetuated and recorded by Burton W. Holt, Registered Land Surveyor No. 418, in 1965, and further perpetuated and recorded by John M. Powell Deputy County Surveyor, in 1966, monumented with an iron post, 1½ ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.				
	<p>COUNTY SURVEYORS OFFICE</p> <p>T 31 S R 3 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 5px;">¼</td> <td style="border-left: 1px solid black; padding-left: 5px;">S 6</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 5px;">S 7</td> </tr> </table> <p>1966</p>	¼	S 6		S 7
¼	S 6				
	S 7				
	<p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A fir snag, 27 ins. diam., bears S. 39½° W., 40 lks. dist., with opened blaze, no marks visible. (Record S. 41½° W., 35½ lks.)</p> <p>and the remains of bearing trees mkd. by Holt</p> <p style="padding-left: 40px;">A fir snag, 20 ins. diam., bears S. 35 3/4° E., 25 lks. dist., with scribe marks ¼ S7 CS BT visible on partially healed double blaze.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 20½° W., 8 lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 32½° W., 37 lks. dist., mkd. ¼ S7 BT.</p>				
	<p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 0° 24' W., bet. secs. 5 and 6.</p>				
1.00	Ascend over S. slope, through heavy timber and light undergrowth. Dirt road, 20 lks. wide, bears N. 50° E. and S. 50° W.				
5.75	Ridge, bears E. and W.; desc. over broken NW. slope.				
19.96	Point for the S 1/16 sec. cor. of secs. 5 and 6.				
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> S 1/16 S 6 S 5 1986 </p>				