

# County Surveyor's Record, Douglas County, Oregon

18336

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 31 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	<p>T 31 S R 3 W</p> <p style="margin-left: 100px;"><math>\frac{1}{4}</math></p> <p style="margin-left: 80px;">S 6   S 5</p> <p style="margin-left: 100px;">1985</p>
	<p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>N. 0° 23' W., beginning new measurement. Ascend over broken SW. slope.</p>
3.85	<p>Spur, slopes N. 80° W.; desc. over broken NW. slope.</p>
15.35	<p>Creek, 1 lk. wide, course N. 70° W.; asc. over broken SW. slope.</p>
29.45	<p>Spur, slopes S. 45° W.; desc. over broken NW. slope.</p>
37.40	<p>Spur, slopes N. 45° W.; desc. over broken NE. slope.</p>
50.75	<p>Creek, 4 lks. wide, course N. 50° W.; asc. over SW. slope.</p>
57.65	<p>Spur, slopes W.; desc. over NW. slope.</p>
59.40	<p>The original closing cor. of secs. 5 and 6, perpetuated and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1959, and further perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1966, monumented with an iron pipe 1½ ins. diam., firmly set, projecting 4 ins. above ground, alongside is an iron post, 1½ ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T30S S32 S5 S6 T31S R3W 1965, from which the original bearing trees:</p> <p style="margin-left: 40px;">A fir, 35 ins. diam., bears S. 57½° E., 24 lks. dist., with healed blaze. (Record, S. 64½° E., 28 lks.)</p> <p style="margin-left: 40px;">A maple, 14 ins. diam., bears S. 37½° W., 28 lks. dist., with rotted blaze, no marks visible. (Record, S. 33° W., 24 lks.)</p> <p>and bearing trees mkd. by Markham</p> <p style="margin-left: 40px;">A fir, 25 ins. diam., bears N. 75° E., 32 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A live oak, 13 ins. diam., bears S. 19½° W., 106 lks. dist. with healed blaze.</p> <p style="margin-left: 40px;">A fir, 22 ins. diam., bears S. 77½° W., 23 lks. dist., with healed blaze.</p> <p>Descend over NW. slope.</p>
59.44	<p>Point for the closing cor. of secs. 5 and 6, at intersection with the S. bdy. of T. 30 S., R. 3 W.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> <p>T 30 S R 3 W</p> <p style="margin-left: 100px;">S 32</p> <hr style="width: 50%; margin: 0 auto;"/> <p style="margin-left: 80px;">S 6   S 5</p> <p style="margin-left: 100px;">C C</p> <p>T 31 S R 3 W</p> <p style="margin-left: 100px;">1986</p> </p> <p>No suitable trees available.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p>