

# County Surveyor's Record, Douglas County, Oregon

18337

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 31 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
	<p>From this point, the <math>\frac{1}{4}</math> sec. cor. of sec. 32 only, T. 30 S., R. 3 W., bears N. 89° 22' E., 2.33 chs. dist., hereinbefore described.</p>
	<p>Subdivision of Section 6, T. 31 S., R. 3 W., Willamette Meridian, Oregon</p>
	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 6 and 7.</p> <p>N. 0° 57' W., on the N. and S. center line of sec. 6.</p> <p>descend over NE. slope, through young timber and dense undergrowth.</p>
0.60	Ravine, drains N. 80° E.; asc. over SE. slope.
7.85	Spur, slopes N. 80° E.; desc. over NE slope.
18.50	<p>Point for the center S <math>\frac{1}{16}</math> sec. cor. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <math display="block">\begin{array}{c} C \\ S \frac{1}{16}   S 6 \\ C \\ 1986 \end{array}</math> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 9 ins. diam., bears N. 1° E., 69 lks. dist., mkd. CS <math>\frac{1}{16}</math> S6 BT.</p> <p style="margin-left: 40px;">A madrone, 6 ins. diam., bears N. 82° W., 22½ lks. dist., mkd. CS <math>\frac{1}{16}</math> S6 BT on the bark.</p> <p style="margin-left: 40px;">Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend over broken N. slope.</p>
30.65	Creek, 2 lks. wide, course N. 65° E. from S. 80° W.; asc. over broken S. slope.
37.00	<p>Point for the center <math>\frac{1}{4}</math> sec. cor. of sec. 6, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <math display="block">\begin{array}{c} T 31 S R 3 W \\ C \frac{1}{4} S 6 \\ 1986 \end{array}</math> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 39 ins. diam., bears N. 60° E., 47 lks. dist., mkd. C<math>\frac{1}{4}</math> S6 BT on bark blaze.</p> <p style="margin-left: 40px;">A fir, 34 ins. diam., bears N. 19° W., 82 lks. dist., mkd. C<math>\frac{1}{4}</math> S6 BT.</p> <p style="margin-left: 40px;">Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over broken SE. slope.</p>
99.37	The $\frac{1}{4}$ sec. cor. of sec. 6 only, on the N. bdy. of the Tp.