

County Surveyor's Record, Douglas County, Oregon

18338

Subdivision of Section 6,
T. 31 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 5 and 6.</p> <p>S. $85^{\circ} 16' W.$, on the E. and W. center line of sec. 6.</p> <p>Descend over steep SW. slope, through moderate timber and undergrowth.</p>
12.15	Creek, 4 lks. wide, course N. $30^{\circ} W.$; asc. over NE. slope.
20.21	<p>Point for the center E $\frac{1}{16}$ sec. cor. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $C \frac{E \frac{1}{16}}{S 6} C$ <p>1986</p> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 15 ins. diam., bears N. $17^{\circ} E.$, $14\frac{1}{2}$ lks. dist., mkd. CE $\frac{1}{16}$ S6 BT.</p> <p style="margin-left: 40px;">A fir, 4 ins. diam., bears S. $33^{\circ} W.$, $43\frac{1}{2}$ lks. dist., mkd. X BT.</p> <p>Ascend over NE. slope.</p>
20.65	Spur, slopes N. $40^{\circ} W.$; desc. over broken NW. slope.
24.45	East Fork Poole Creek, 6 lks. wide, course N. $15^{\circ} E.$; asc. over broken SE. slope.
40.42	<p>The center $\frac{1}{4}$ sec. cor. of sec. 6.</p> <p>Ascend over broken SE. slope.</p>
67.85	Ridge, bears N. $10^{\circ} E.$ and S. $10^{\circ} W.$; desc. over broken W. slope.
83.75	<p>The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, on the W. bdy. of the Tp., monumented with a stainless steel post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $T 31 S$ $R 4 W \quad R 3 W$ $S 1 S6$ <p>1985</p> </div> <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A fir, 30 ins. diam., bears N. $61\frac{1}{4}^{\circ} E.$, 23 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A decayed fir stump, size indeterminate, bears S. $57\frac{1}{2}^{\circ} W.$, $25\frac{1}{2}$ lks. dist., no marks visible.</p> <p>and the remains of bearing trees mkd. by John H. Markham, Jr., Registered Engineer NO. 2880, in 1960</p> <p style="margin-left: 40px;">A root hole, bears N. $44^{\circ} E.$, 15 lks. dist., with down maple alongside, 14 ins. diam., with healed blaze.</p> <p style="margin-left: 40px;">A root hole, bears S. $58^{\circ} E.$, 29 lks. dist., with down fir alongside, 8 ins. diam., with scribe marks $\frac{1}{4}$ S6 BT visible on partially healed blaze.</p> <p style="margin-left: 40px;">A madrone, 14 ins. diam., bears S. $59^{\circ} W.$, 29 lks. dist., with scribe marks $\frac{1}{4}$ S1 BT visible on bark blaze.</p> <p style="margin-left: 40px;">A fir, 6 ins. diam., bears N. $49^{\circ} W.$, 10 lks. dist., with healed blaze.</p>