

County Surveyor's Record, Douglas County, Oregon

18339

Subdivision of Section 6,
T. 31 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
	<p>From this point, United States Geological Survey triangulation station "BLAND MTN 1953" bears N. 5° 04' W., 347.83 chs. dist., monumented with a brass tablet, 4 ins. diam., cemented flush with top of bedrock, with top mkd. U S GEOLOGICAL SURVEY BLAND MTN 1953 and a triangle.</p>
6.55	<p>From the E 1/16 sec. cor. of secs. 6 and 7.</p> <p>N. 0° 34' W., on the N. and S. center line of the SE$\frac{1}{4}$ of sec. 6.</p> <p>Descend over steep, broken N. slope.</p> <p>Ravine, drains N. 55° W.; desc. over broken NW. slope.</p>
19.24	<p>Point for the SE 1/16 sec. cor. of sec. 6, at intersection with the E. and W. center line of the SE$\frac{1}{4}$.</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S 6 1986</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 48 ins. diam., bears N. 57° E., 53 lks. dist., mkd. SE 1/16 S6 BT.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. 70$\frac{1}{2}$° W., 50 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend along broken W. slope.</p>
37.90	<p>Spur, slopes N. 40° W.; desc. over NE. slope.</p>
38.46	<p>The center E 1/16 sec. cor. of sec. 6.</p>
19.98	<p>From the S 1/16 sec. cor. of secs. 5 and 6.</p> <p>S. 87° 19' W., on the E. and W. center line of the SE$\frac{1}{4}$ of sec. 6.</p> <p>Descend over steep, broken NW. slope.</p> <p>The SE 1/16 sec. cor. of sec. 6.</p> <p>Descend over NW. slope.</p>
22.30	<p>East Fork Poole Creek, 4 lks. wide, course N. 20° W.; asc. over broken E. slope.</p>
40.02	<p>The center S 1/16 sec. cor. of sec. 6.</p>
<p>Subdivision of Section 28, T. 31 S., R. 3 W., Willamette Meridian, Oregon</p>	
20.06	<p>From the 1/4 sec. cor. of sec. 28 only, on the S. bdy. of the section.</p> <p>N. 0° 41' W., on the N. and S. center line of sec. 28.</p> <p>Descend over a NW. slope, through heavy timber and dense undergrowth.</p> <p>Point for the center S 1/16 sec. cor. of sec. 28.</p>