

County Surveyor's Record, Douglas County, Oregon

Corrective Dependent Resurvey of a Portion of
the Subdivisional Lines, T. 30 S., R. 5 W., **18349**
Willamette Meridian, Oregon

CHAINS

- 21.85 Creek, 2 lks. wide, course S. 10° W.; asc. over broken SE. slope.
- 38.60 Spur, slopes S. 20° E.; desc. over SW. slope.
- 39.45 The cor. of secs. 9, 10, 15, and 16, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 30 S R 5 W

S 9	S 10
S 16	S 15

 1969

from which bearing trees mkd. by Roseberry and Jelley

- A fir, 11 ins. diam., bears N. 74½° E., 24 lks. dist., with healed blaze.
- A fir, 32 ins. diam., bears S. 57½° E., 49 lks. dist., with healed blaze.
- A fir, 18 ins. diam., bears S. 13½° W., 44½ lks. dist., with healed blaze.
- A fir, 23 ins. diam., bears N. 58° W., 13 lks. dist., with healed blaze.

The following field notes describe the remonumentation and rehabilitations of certain corner points, T. 30 S., R. 5 W., Willamette Meridian, Oregon, as provided for in the Special Instructions, Group No. 1000, Oregon, dated July 13, 1979, "Investigation of Physical evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, with New Accessories When Needed" and the Supplemental Special Instructions, Group No. 1000, Oregon, dated May 20, 1985, "Rehabilitation of Corner Points, Without Remonumentation, When Suitable Monumentation Exists."

The remonumentation and rehabilitation of these corner points was made at the request of the Roseburg District Manager for administrative purposes of the Bureau of Land Management.

Remonumentation and/or Rehabilitation of Certain Corner Points,
T. 30 S., R. 5 W., Willamette Meridian, Oregon

(Remonumenting and/or rehabilitating corners established by Nathaniel Ford, in 1854, established or reestablished by Oscar F. Thiel, in 1896, and established or reestablished by Lynn M. Roseberry and James E. Jelley, in 1967-69)

The ¼ sec. cor. of secs. 9 and 10, monumented with the original corner tree, a fir snag, 18 ins. diam., with scribe mark S visible on opened blaze on W. face, from which the remains of bearing trees mkd. by Roseberry and Jelley:

- A fir snag, 11 ins. diam., bears S. 34½° E., 87½ lks. dist. with scribe marks ¼ S10 BT visible on partially healed blaze.
- A cedar, 30 ins. diam., bears N. 85½° W., 196½ lks. dist., with healed blaze.

and a new bearing tree

- A fir, 7 ins. diam., bears N. 54° E., 39 lks. dist., mkd. ¼ S10 BT.