

County Surveyor's Record, Douglas County, Oregon

18350

Remonumentation and/or Rehabilitation of Certain Corner Points,
T. 30 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

From this point, a local corner, established by James W. Byron, Deputy County Surveyor, in 1959, bears South, 0.02 chs. dist., monumented with an iron post, 1½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

½ S | S
9 | 10
T 30 S R 5 W
1959

from which the remains of a bearing tree mkd. by Byron

A fir snag, 10 ins. diam., bears N. 46° E., 67 lks. dist., with healed blaze.

and the remains of a bearing tree of no known record

A decayed fir stump, 32 ins. diam., bears S. 78½° E., 16 lks. dist., with scribe marks BT visible on opened blaze.

The N 1/16 sec. cor. of secs. 16 and 17 (the corner monument was uprooted and lying alongside nearby fence corner), determined at record bearing and distance from bearing trees mkd. by Roseberry and Jelley:

A fir, 17 ins. diam., bears S. 89° E., 193½ lks. dist., with healed blaze.

A fir snag, 30 ins. diam., bears N. 62° W., 396 lks. dist., with healed blaze.

At the corner point

Reset the iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

N 1/16
S 17 | S16
1969

from which a new bearing tree

A fir, 9 ins. diam., bears S. 75½° W., 149 lks. dist., mkd. N 1/16 S17 BT.

The corner lies S. 83° E., 0.40 chs. dist. from a fence corner, with fences extending N., S., and W.

The cor. of secs. 8, 9, 16, and 17, determined at record bearing and distance from bearing trees mkd. by Roseberry and Jelley:

A pine, 18 ins. diam., bears N. 57° E., 186 lks. dist., with healed blaze.

A madrone, 16 ins. diam., bears S. 57½° E., 179 lks. dist., with healed blaze.

A pine, 22 ins. diam., bears S. 43½° W., 244 lks. dist., with healed blaze.

A fir, 20 ins. diam., bears N. 26° W., 148 lks. dist., with healed blaze.

At the corner point