

County Surveyor's Record, Douglas County, Oregon

18356

Dependent Resurvey of a Portion of the East Boundary,
T. 30 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

and new bearing trees

A fir, 9 ins. diam., bears S. 36° W., 104 lks.
dist., mkd. T30S R9W S25 BT.

A fir, 6 ins. diam., bears N. 27° W., 85½ lks.
dist., mkd. T30S R9W S24 BT.

From the cor. of secs. 7, 12, 13, and 18, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1958, and further perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1964, monumented with an iron post, 1½ ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S
R S 12 | S 7 R
9 S 13 | S 18 8
W W

1958

from which the remains of the original bearing trees

A fir stump, 40 ins. diam., bears S. 48° E., 117 lks. dist., with healed blaze. (Record, 114 lks.)

A rotted pine stump, 15 ins. diam., bears N. 12° W., 30 lks. dist., with scribe marks BT visible on a rotted blaze. (Record, 29 lks.)

A rotted fir stump, size indeterminate, bears N. 45° E., 50 lks. dist., no marks remaining.

and the remains of the bearing trees mkd. by Byron

A fir, 12 ins. diam., bears N. 73° E., 44 lks. dist., with healed blaze.

A fir, 16 ins. diam., bears S. 30° E., 16 lks. dist., with healed blaze.

A chinquapin, 13 ins. diam., bears S. 43° W., 54 lks. dist., with a rotted blaze.

A root hole, bears N. 89° W., 14 lks. dist., with a downed fir, 9 ins. diam., lying alongside, with scribe marks R9W CS visible on a rotted blaze.

and a bearing tree mkd. by Tracy

A fir, 21 ins. diam., bears N. 71° W., 83 lks. dist., with two healed blazes.

and a new bearing tree

A fir, 4 ins. diam., bears N. 22° W., 22 lks. dist., mkd. X BT.

N. 0° 04' W., bet. secs. 7 and 12.

Descend over broken N. slope, through heavy timber and dense undergrowth.