

County Surveyor's Record, Douglas County, Oregon

18358 Dependent Resurvey of a Portion of the East Boundary
T. 30 S., R.9 W., Willamette Meridian, Oregon

CHAINS											
	<p>A fir, 22 ins. diam., bears S. 67° E., 24 lks. dist., with healed blaze.</p> <p>A fir, 19 ins. diam., bears S. 8° W., 58 lks. dist., with healed blaze.</p> <p>A fir, 33 ins. diam., bears N. 36° W., 68 lks. dist., with healed blaze.</p>										
	<p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 30 S., R. 9 W., Willamette Meridian, Oregon</p>										
	<p>(Restoring the survey by Dennis Hathorn, in 1855, and the survey by William M. Bushey, in 1893)</p>										
	<p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the tp. N. 89° 51' W., bet. secs. 25 and 36.</p> <p>Descend over broken SW. slope, through scattering timber and dense undergrowth.</p>										
25.30	<p>Creek, 3 lks. wide, course S. 10° E.; asc. over E. slope.</p>										
39.76	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 30 S R 9 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">$\frac{1}{4}$</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 25</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding: 0 5px;">S 36</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">1986</td> </tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 4 ins. diam., bears N. 25$\frac{1}{2}$° E., 90 lks. dist., mkd. X BT.</p> <p style="margin-left: 40px;">A fir, 7 ins. diam., bears S. 48$\frac{1}{2}$° E., 25 lks. dist., mkd. $\frac{1}{4}$ S36 BT.</p> <p style="margin-left: 40px;">Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over broken NE. slope.</p>	$\frac{1}{4}$	S 25		S 36		1986				
$\frac{1}{4}$	S 25										
	S 36										
	1986										
60.10	<p>Top of ascent, bears NW. and SE.; desc. over steep W. slope.</p>										
79.52	<p>The cor. of secs. 25, 26, 35 and 36, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1964, monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 12 ins. above ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEYORS OFFICE</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="padding: 0 5px;">T 30 S</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 26</td> <td style="padding: 0 5px;">S 25</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 35</td> <td style="padding: 0 5px;">S 36</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">R 9 W</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">1964</td> </tr> </table> </div> <p>from which an original bearing tree</p> <p style="margin-left: 40px;">A cedar, 47 ins. diam., bears N. 1° W., 249 lks. dist., with healed blaze. (Record 243 lks.)</p>	T 30 S		S 26	S 25	S 35	S 36	R 9 W		1964	
T 30 S											
S 26	S 25										
S 35	S 36										
R 9 W											
1964											