

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines **18359**
T. 30 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	<p>and the remains of the bearing trees mkd. by Bushey</p> <p style="padding-left: 40px;">A fir, 38 ins. diam., bears N. 41½° E., 25½ lks. dist., with illegible scribe marks visible on an opened blaze.</p> <p style="padding-left: 40px;">A decayed pine stump, 40 ins. diam., bears S. 59° E., 178 lks. dist., with scribe marks 5 B visible on a burnt blaze. (Record, 173 lks.)</p> <p>and bearing trees mkd. by Tracy</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 70° E., 37 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 45° E., 40 lks. dist., with two healed blazes.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears South, 22 lks. dist., with two healed blazes.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 19° W., 31 lks. dist., with healed blaze.</p>
	<p>N. 0° 07' W., bet. secs. 25 and 26.</p> <p>Cross broken W. slope, through scattering timber and dense undergrowth.</p>
8.40	Ravine, drains W.; asc. over SW. slope.
23.70	Spur, slopes NW.; desc. over steep N. slope.
39.70	Twelvemile Creek, 20 lks. wide, course N. 60° E.; asc. over SE. slope.
39.84	<p>The ¼ sec. cor. of secs. 25 and 26, perpetuated and recorded by Howard W. Johnstone, Registered Land Surveyor No. 498, in 1964, and further perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1964, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p>
	<p>COUNTY SURVEYORS OFFICE</p> <p>T 30 S</p> <p>¼ S 26 S 25</p> <p>R 9 W</p> <p>1964</p>
	<p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A fir root crown, bears N. 19° W., 32 lks. dist., no marks remain.</p> <p>and a bearing tree mkd. by Johnstone.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 78° E., 107 lks. dist., with healed double blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">An alder, 8 ins. diam., bears S. 60° W., 15½ lks. dist., mkd. ¼ S26 BT on the bark.</p>
	<p style="text-align: center;">—————</p> <p>N. 0° 35' W., beginning new measurement</p> <p>Ascend over steep SE. slope, through scattering timber and dense undergrowth.</p>