

County Surveyor's Record, Douglas County, Oregon

18360 Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

- 1.80 Gravel road, 35 lks. wide, bears NE. and SW.
- 7.60 Spur, slopes E.; cross over broken E. slope.
- 19.30 Begin descent over NE. slope.
- 20.18 Point for the N 1/16 sec. cor. of secs. 25 and 26.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

N 1/16
S 26 | S 25
1986

from which

 - A yew, 12 ins. diam., bears N. 1° E., 24 lks. dist., mkd. N 1/16 S25 BT.
 - A fir, 8 ins. diam., bears S. 79° W., 49 lks. dist., N 1/16 S26 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Continue over NE. slope.
- 20.90 Creek, 1 lk. wide, course E.; asc. over SE. slope.
- 26.10 Spur, slopes S. 80° E., desc. over NE. slope.
- 29.90 Gravel road, 30 lks. wide, bears N. 30° W. and S. 30° E.
- 30.27 Point for the N-N 1/64 sec. cor. of secs. 25 and 26.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 30 ins. in the ground, with top 2 ins. below the surface, with brass cap mkd.

NN 1/64
S 26 | S 25
1986

from which

 - A fir, 4 ins. diam., bears S. 84½° E., 94 lks. dist., mkd. X at breast height and BT at the base.
 - A fir, 9 ins. diam., bears S. 27° W., 104½ lks. dist., mkd. NN 1/64 S26 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

The corner is located on the east shoulder of gravel road, 30 lks. wide, bears N. 30° W. and S. 30° E.

Cross broken E. slope, through a logged area.
- 40.36 The cor. of secs. 23, 24, 25 and 26, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1964, monumented with an iron post, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 30 S
23 | 24
26 | 25
R 9 W
1964