

# County Surveyor's Record, Douglas County, Oregon

18361

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 30 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

from which the remains of the original bearing trees

A root hole, bears N. 16° E., 25 lks. dist.,  
with a decayed fir, of indeterminate size,  
lying along side, no marks remaining.

A sawed fir stump, 24 ins. diam., bears  
S 62½° E., 11 lks. dist., with scribe marks  
T30S R9W S 25 BT visible on an opened blaze.  
(Record, S. 70° E., 9 lks.)

A sawed fir stump, 15 ins. diam., bears  
S. 47° W., 16 lks. dist., with scribe  
marks S26 BT visible on an opened blaze.  
(Record, S. 40° W., 11 lks.)

A sawed fir stump, 22 ins. diam., bears  
N. 27° W., 24 lks. dist., no visible marks

and the remains of the bearing trees mkd. by Tracy

A fir, 16 ins. diam., bears N. 69½° E., 132  
lks. dist., with illegible scribe marks on  
a partially healed blaze.

A sawed fir stump, 15 ins. diam., bears  
S. 58° W., 208 lks. dist., with a rotted blaze.

and new bearing trees

A fir, 6 ins. diam., bears S. 22° E., 21½ lks.  
dist., mkd. T30S R9W S25 BT.

A fir, 9 ins. diam., bears S. 22° W., 11 lks.  
dist., mkd. T30S R9W S26 BT.

A fir, 7 ins. diam., bears N. 39½° W., 7 lks.  
dist., mkd. T30S R9W S23 BT.

From the cor. of secs. 19, 24, 25 and 30, on the E.  
bdy. of the Tp.

N. 89° 31' W., bet. secs. 24 and 25.

Descend over NW. slope, through a logged area.

1.20 Dry creek bed, drains N.; asc. over broken NE. slope.

23.60 Leave logged area, edge bears N. and S.; enter heavy  
timber and dense undergrowth.

28.50 Spur, slopes N.; desc. over NW. slope.

33.20 Ravine, drains N.; asc. over NE. slope along the S. edge  
of a logged area.

39.95 The 1/4 sec. cor. of secs. 24 and 25, determined from  
the remaining original bearing tree:

A sawed fir stump, 36 ins. diam., bears  
N. 66° E., 115 lks. dist., with reverse scribe  
mark B visible on the overgrowth of an opened  
blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam.,  
24 ins. in the ground, with brass cap mkd.