

County Surveyor's Record, Douglas County, Oregon

18363

Subdivision of Section 25,
T. 30 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brss cap mkd.</p> <p style="text-align: center;">T 30 S R 9 W C ¼ S 25 1986</p> <p>from which</p> <p>A fir, 26 ins. diam., bears N. 79¼° E., 24 lks. dist., mkd. C¼ S25 BT.</p> <p>A fir, 10 ins. diam., bears N. 48° W., 37 lks. dist., mkd. C¼ S25 BT.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Continue over NW. slope.</p>
54.90	Gravel road, 30 lks.wide,bears N. 10° E. and S. 10° W.
59.96	Point for the center N 1/6 sec. cor. of sec. 25.
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 S R 9 W C N 1/16 S 25 C 1986</p> <p>A fir, 31 ins. diam., bears N. 21° E., 13 lks. dist., mkd. CN 1/16 S25 BT.</p> <p>A fir, 27 ins. diam., bears S. 68½° E., 29 lks. dist., mkd. CN 1/16 S25 BT.</p> <p>Continue over NW. slope.</p>
77.20	Spur, slopes N. 20° W.; continue to desc. over NE. slope.
79.99	The ¼ sec. cor. of secs. 24 and 25.
	<p>From the ¼ sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp. N. 89° 59' W., on the E. and W. center line of sec. 25.</p> <p>Descend over broken NW. slope, through a logged area.</p>
2.20	Gravel road, 30 lks. wide, bears N. 10° E. and S. 10° W.
8.00	Ravine, drains N.; asc. over NE. slope.
13.60	Gravel road, 30 lks. wide, bears NW. and SE.
22.50	Gravel road, 20 lks. wide, on ridge bearing NW. and SE.; desc. over broken NW. slope, through heavy timber and dense undergrowth.
39.76	The center ¼ sec. cor. of sec. 25.
	Continue over NW. slope, through a logged area.
46.20	Gravel road, 30 lks. wide, bears N. 20° E. and S. 20° W.
59.56	Point for the center W 1/16 sec. cor. of sec. 25.