

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 25,
T. 30 S., R. 9 W., Willamette Meridian, Oregon

18365

| CHAINS | |
|--------|--|
| 30.15 | <p>Point for the center N-NW 1/64 sec. cor. of sec. 25.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 25 C-N NW 1/64 1986</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 89° E., 18 lks. dist., mkd. CN NW 1/64 S25 BT.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 62° W., 11½ lks. dist., mkd. CN NW 1/64 S25 BT.</p> <p>Continue over SW. slope.</p> |
| 33.90 | Spur, slopes N. 70° W.; desc. over NW. slope. |
| 36.20 | Dry creek bed, drains W.; asc. over SW. slope. |
| 37.90 | Spur, slopes W.; desc. over NW. slope. |
| 39.20 | Ravine, drains W.; asc. over SW. slope. |
| 40.19 | The W 1/16 sec. cor. of secs. 24 and 25. |
| | <p>From the center N 1/16 sec. cor. of sec. 25.</p> <p>N. 89° 45' W., on the E. and W. center lien of the NW¼ of sec. 25.</p> <p>Descend over broken NW. slope, through ehavy timber and dense undergrowth.</p> |
| 12.70 | Gravel road, 30 lks. wide, bears N. 5° W. and S. 5° E.; enter logged area. |
| 19.83 | <p>The NW 1/16 sec. cor. of sec. 25.</p> <p>Continue over broken NW. slope.</p> |
| 32.00 | Twelvemile Creek, 50 lks. wide, course N. 30° E.; asc. over broken E. slope. |
| 37.60 | Gravel road, 30 lks. wide, bears N. 40° W. and S. 20° E. |
| 39.66 | The N 1/16 sec. cor. of secs. 25 and 26. |
| | <p>From the center N-NW 1/64 sec. cor. of sec. 25.</p> <p>N. 89° 39' W., on the E. and W. center line of the NW¼ of the NW¼ of sec. 25.</p> <p>Descend over NW. slope, through scattering timber and dense undergrowth.</p> |
| 4.00 | Twelvemile Creek, 30 lks. wide, coursse N. 25° W.; asc. over broken NE. slope. |
| 19.85 | The N-N 1/64 sec. cor. of secs. 25 and 26. |