

# County Surveyor's Record, Douglas County, Oregon

18373

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 31 S., R. 8 W., Willamette Meridian, Oregon

CHAINS							
38.40	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 2 and 11 at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 31 S R 8 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">S 2</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 10px;"><math>\frac{1}{4}</math> S 11</td> </tr> <tr> <td style="padding: 0 10px;">1986</td> </tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 10 ins. diam., bears S. <math>2^\circ</math> E., 18 lks. dist., mkd. <math>\frac{1}{4}</math> S11 BT.</p> <p style="margin-left: 40px;">A fir, 6 ins. diam., bears N. <math>27^\circ</math> W., <math>23\frac{1}{2}</math> lks. dist., mkd. <math>\frac{1}{4}</math> S2 BT.</p> <p>Deposit white DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend over broken NW. slope.</p>	S 2	$\frac{1}{4}$ S 11	1986			
S 2							
$\frac{1}{4}$ S 11							
1986							
67.10	Creek, 3 lks. wide, course S. $70^\circ$ W.						
67.60	Creek, 5 lks. wide, course S. $20^\circ$ W.; desc. over broken W. slope.						
74.40	Asphalt road, 30 lks. wide, bears N. $20^\circ$ W. and S. $20^\circ$ E.						
75.70	Union Creek, 15 lks. wide, course S. $15^\circ$ E.; asc. over E. slope.						
76.80	<p>The cor. of secs. 2, 3, 10, 11, monumented with an iron post. <math>2\frac{1}{2}</math> ins. diam., firmly set, extending 8 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 31 S R 8 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">S 3</td> <td style="padding: 0 10px;">S 2</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 10px;">S 10</td> <td style="border-top: 1px solid black; padding: 0 10px;">S 11</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">1961</td> </tr> </table> </div> <p>from which an original bearing tree</p> <p style="margin-left: 40px;">A cedar, 35 ins. diam., bears S. <math>66^\circ</math> E., 46 lks. dist., with chopped out blaze, no marks visible.</p> <p>and the remains of bearing trees mkd. by White, Corbin, and Beck</p> <p style="margin-left: 40px;">A hemlock snag, 20 ins. diam., bears S. <math>54^\circ</math> E., 49 lks. dist., with rotted out blaze, no marks visible. (Record, S. <math>56^\circ</math> E., 45 lks.)</p> <p style="margin-left: 40px;">A hemlock, 30 ins. diam., bears S. <math>85^\circ</math> W., 120 lks. dist., with healed blaze. (Record, 124 lks.)</p> <p>and bearing trees mkd. by M. Lenora Ladig, deputy County Surveyor, in 1976</p> <p style="margin-left: 40px;">An alder, 8 ins. diam., bears N. <math>2^\circ</math> E., 31 lks. dist., with scribe marks T31S R8W 2 CS BT visible on partially healed blaze.</p> <p style="margin-left: 40px;">A yew, 8 ins. diam., bears S. <math>56^\circ</math> E., 44 lks. dist., with healed blaze.</p> <p>and new bearing trees</p> <p style="margin-left: 40px;">An alder, 8 ins. diam., bears N. <math>69^\circ</math> E., 26 lks. dist., mkd. T31S R8W S2 BT on the bark</p>	S 3	S 2	S 10	S 11	1961	
S 3	S 2						
S 10	S 11						
1961							